

# ICIP-D2360

## 2 Megapixel Indoor, 360° Network Dome Camera

---



2.0 Megapixel 360° Indoor Dome camera with Built In Microphone. The ICIP-D2360 series camera is a realtime, 360° situational awareness camera. It is capable of recording a wide area of surveillance, and dewarping the native FishEye view in order to watch a stream that is undistorted to the human eye.

### Features

- 1/3" 2Megapixel Exmor CMOS
- ONVIF Profile S
- PoE (802.3af)
- Micro SD



# ICIP-D2360

## Specifications

<b>Model</b>	ICIP-D2360
<b>Camera</b>	
Image Sensor	1/3" 2Megapixel Exmor CMOS
Effective Pixels	1920(H)×1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/4~1/10000
Min. Illumination	Color: 0. 1LUX/F1.4
S/N Ratio	< 50dB
<b>Camera Features</b>	
Day/Night	Auto(Electronic)/Color/B/W
Backlight Compensation	BLC
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas
<b>Lens</b>	
Focal Length	1.25mm
Max Aperture	F1.8
Angle of View	H: 180°±5°
Mount Type	Board-in Type
<b>Video</b>	
Compression	H.264 / MJPEG
Resolution	1080P(1920x1080)/ SXGA(1280x1024)720P(1280x720)/ D1(704x576) / CIF(352x288)
Frame Rate	Main Stream - 4M(1~15fps)/ 3M (1 ~ 25/30fps) Sub Stream - D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Profile S
Max. User Access	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>General</b>	
Power Supply	DC12V, PoE (802.3af)
Memory Slot	Micro SD
Power Consumption	< 2.5W
Working Environment	-10°C ~ 60°C, 10%~90%
Dimensions (D×H)	Φ110×54mm
Weight	0.25kg

# ICIP-D2360

---

## Optional Accessories



**MNT-ARM-MPB300S**



**MNT-BOX-MPA120**



**MNT-CEILING-MPA**



**MNT-DVIR-MPA100**



**MNT-PCNRIP**



**MNT-POLIP**