

ICIP-D3000VIR-I

3 MP Indoor/Outdoor, Vandalproof Full-Size IR Dome IP Camera



A rugged, day/night, outdoor rated 3 Megapixel IP dome camera - the ICIP-D3000VIR-I. Featuring a hardened dome chassis, the ICIP-D3000VIR-I is IK10 impact resistant, and IP66 weatherproof, making it well suited as a vandal resistant camera. Contained inside is a high resolution 3 Megapixel Aptina CMOS imager, capable of outputting a crystal clear image. The optics include a vari-focal 3~9mm motorized varifocal lens. IR LEDs on this unit are suitable for viewing up to 60' with 0 light. This camera also comes equipped with an audio input for external microphones, alarm I/O's, and support for PoE power.

Features

- 3MP Aptina CMOS
- Onboard Simple Analytics
- IK10 & IP66
- 3 ~ 9mm Motorized Varifocal Lens
- Supports PoE, Alarm I/O's & Audio connection

ICIP-D3000VIR-I

Specifications

Model	ICIP-D3000VIR-I
Camera	
Image Sensor	1/3" 3Megapixel Aptina CMOS
Effective Pixels	2048(H)×1536(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual 1/3~1/10000
Min. Illumination	Color: 0. 1Lux/F1.2, B/W: 0.01Lux/F1.2
S/N Ratio	More than 50dB
Video Output	1 port
Camera Features	
Max. IR LEDs Length	60'/20m - Smart IR technology
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR (120dB)
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
EIS	Support
Ultra Defog	Support
Lens	
Focal Length	3 ~ 9mm motorized
Max Aperture	F1.4
Focus Control	Auto
Angle of View	H: 86.5° (Wide) ~ 28.6° (Tele)
Lens Type	Motorized / Auto Iris (DC)
Mount Type	Board-in Type
Video	
Compression	H.264 / MJPEG
Resolution	3MP (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×480) / CIF (352×240)
Frame Rate	Main Stream - 3MP/1080P (1 ~ 25/30fps) Sub Stream - D1/CIF(1 ~ 25/30fps) Third Stream - 1080P/720P/D1(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps
ROI	Up to 4 areas
Audio	
Compression	G.711a / G.711u
Interface	1/1 channel In/Out
Smart Function	
Smart Detection	Tripwire Intrusion Scene change Missing / Abandoned Audio detect Face detect

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 64GB
Alarm	1/1 channel In/Out
General	
Power Supply	DC12V/AC24V, PoE (802.3af)
Power Consumption	< 12W (IR on: +2W)
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C , Less than 95%RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ5.94"×4.69"/Φ151mm×119mm
Weight	2.76lbs/1.25kg

ICIP-D3000VIR-I

Accessories



[MNT-ARM-MPB300S](#)



[MNT-BOX-MPA120](#)



[MNT-DVIR-MPA100](#)



[MNT-PCNRIP](#)



[MNT-POLIP](#)