

ICIP-S1300WDR

1.3 Megapixel Indoor, Box Network Camera



Affordable, and feature rich, high resolution IP box camera – the ICIPS1300WDR. This common box style design contains features that are anything but common. Contained inside, is a power 1.3 Megapixel Aptina CMOS sensor, capable of outputting a crisp, clear image. This camera accepts a wide array of standard C/CS mount lenses, enabling lots of viewing possibilities. This camera is fully accessible via the entire ICR software suite, and is also compatible with third party ONVIF recorders and streamers. This camera also comes equipped with an audio input for external microphones, alarm I/O's, and support for POE power.

Features

- Accepts C/CS mount lenses
- Wide Dynamic Range
- PoE, DC12V/AC24V PS
- Built-in 1/1 alarm in/out
- Audio Input
- 1/3" 1.3Megapixel progressive scan Aptina CMOS

ICIP-S1300WDR

Specifications

Model	ICIP-S1300WDR
Camera	
Image Sensor	1/3" 1.3Megapixel progressive scan Aptina CMOS
Effective Pixels	1280(H)×960(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/4~1/10000s
Min. Illumination	0. 1LUX/F1.2 (Color), 0.005LUX/F1.2(B/W)
S/N Ration	>50dB
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Camera Features	
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / WDR (128dB)
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas
Lens	
Lens Type	C/CS
Video	
Compression	H.264 / MJPEG
Resolution	1.3M(1280x960) / 720P(1280x720) / D1(704x480) / CIF(352x240) /
Frame Rate	Main Stream: 1.3M/720P(1 ~ 25/30fps) Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps
Audio	
Compression	G.711a / G.711u(64kbps)/PCM(128kbps)
Interface	1/1 channel In/Out
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Ver. 2.0
Max. User Access	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	SD, Max 32GB
RS485	1
Alarm	1/1 channel In/Out
General	
Power Supply	DC12V/AC24V, PoE(802.3af)
Power Consumption	<6W
Working Environment	-14°F ~ 140°F / -25°C ~ 60°C, 10%~90%
Dimensions (W×D×H)	2.76" × 5.90" × 2.49" 70mm × 150mm × 63.2mm

Weight	1.43lb ~ 650g ~ 22.93oz
--------	-------------------------

ICIP-S1300WDR

Optional Accessories



[OUTDOOR HOUSING](#)



[M4](#)