



## KEZ-c2TR3XXIR HD-TVI 1080P Fixed EXIR Outdoor Turret

### Features:

- High resolution SONY 1/2.8" 2.1MP Progressive Color CMOS Image Sensor, 1080p(1920x1080)@30fps
- Support various digital video output 1080p@30fps / 1080p@25fps / 720p@30fps / 720p@25fps
- HD-TVI (HD-Transport Video Interface) Output HD-TVI is suitable for long reach transmission over single coaxial cable. Transmission Distance: 300 m (Color) Max. Transmission Distance: 500 m
- Full-time CVBS output for convenient installation and ease of service.
- IP67 Weatherproof
- OSD menu for setup and configuration
- 2pcs Super Beam LED for 0 Lux viewing performance and range to 130' (40 m)
- Provides True Day/Night capability with motorized IR cut filter
- UTC (Up the coax.) via HD-TVI coaxial cable.
- Power source: 12VDC

<b>Imaging Device</b>	1/2.8" SONY Exmor CMOS Sensor
<b>Video Format</b>	Main Output: 1080p/720p HD-TVI 30/25FPS (OSD selectable) Secondary Output: Full time CVBS (OSD selectable NTSC/PAL) aux video
<b>Picture Elements</b>	2000(H) x 1241(V)
<b>Effective Picture Elements</b>	1920 (H) x 1080 (V)
<b>Horizontal Resolution</b>	More than 1080 HTVL (1080p mode)
<b>Sensitivity</b>	0 lux IR on
<b>Day/Night Type</b>	True Day/Night with ICR motorized filter control
<b>Lens Type</b>	2.8mm
<b>IR LED</b>	2 Super Beam LEDs
<b>IR Range</b>	130' / 40m
<b>Smart IR Exposure Adjust</b>	AUTO
<b>Video Output Connector Type</b>	TVI and CVBS: BNC 75Ω
<b>Sync. Mode</b>	Internal
<b>OSD Languages</b>	English, Spanish, Portuguese, German, Russian, Japanese, French
<b>UTC Control</b>	Full OSD Menu access via up-the-cable (Coaxitron® type ) signaling
<b>DWDR/BLC/HSBLC</b>	OFF/DWDR/BLC/HSBLC Selectable Adjustable for Level 1~10; also BLC area, HLC color.
<b>Auto Gain Control</b>	OFF/Low/Middle/High
<b>Electronic Shutter</b>	Auto;FLK ; or Manual 1/30 (25) to 1/100,000
<b>White Balance</b>	ATW / Push Lock / Manual
<b>Color Correction</b>	Gamma 0.45~.65, adjustable
<b>Day &amp; Night</b>	Auto True D/N with motorized ICR, controlled by photo sensor. Optional color-only and B/W only modes under OSD control
<b>2D-DNR</b>	Off/Low/Mid/High
<b>Mirror</b>	Off / H-flip, V-flip, rotate
<b>Motion Detection</b>	Off/On for programmable zone with sensitivity adjust (pixel change detection), 4 Areas
<b>Privacy Mask</b>	Off/On with full programmability for 4 selectable zones
<b>Lens Shading Compensation</b>	Off/On
<b>DPC (Defective Pixel Correction)</b>	AUTO
<b>Other OSD Functions</b>	Camera Title with position, Font Color; Image Sharpness
<b>Power Source</b>	12VDC
<b>Power Consumption</b>	12VDC:500mA
<b>Operating Temperature</b>	-22 °F ~ 122 °F (-30 °C ~ 50 °C)
<b>Environmental</b>	IP67 weatherproof
<b>Mechanical</b>	Metal ball and base, with base removable for easy mounting
<b>Positioning</b>	3-axis flexible positioning for wall or ceiling mounting Pan: 0~360° Tilt: 0~70° Rotate: 0~360°
<b>Dimensions</b>	5.7" (L) x 5.23" (W) x 4.04" (H))
<b>Weight</b>	1.6 lbs./ .5kg
<b>Certifications</b>	CE,FCC

### Ordering Info:

**KEZ-c2TR3XXIR: HD-TVI 1080P Fixed EXIR Indoor Turret**

KT&C America, Inc. reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

### KT&C America, Inc.

New Jersey Office  
40 Lane Road 1st Floor  
Fairfield, NJ 07004  
T: 973-276-0118  
F: 973-276-0116

New York Office  
200 Pkwy Drive South Suite 200  
Hauppauge, NY 11788  
T: 631-864-0118  
F: 631-864-0116

California Office  
3240 Wilshire Blvd Suite 501  
Los Angeles, CA 90010  
T: 213-381-0061  
F: 213-381-0064

www.ktncusa.com