

1.3MP Corner Mount Vandal Proof IP-Camera



IPC-13MP720EV - 1.3-Megapixel H.264 ONVIF IP All-Weather 2.9mm Vandal-Proof Corner Mount Camera

Vandal-Proof 1.3-MegaPixel ONVIF + PoE Ready, Corner Mount IP Network Camera features an ultra wide-angle 2.9mm lens and low-profile design. Perfect for elevators, schools, hallways, offices and other confined spaces.




ADVANTAGES

- Hi-Def H.264 2-MegaPixels (1920 x 1080) @ 30fps
- Ultra Wide-Angle 2.9mm Lens for Confined Spaces
- Rugged Vandal-Resistant Corner Mount Design
- ONVIF 2.0 Compliant & PoE Ready for Easy Installation
- Easy to Configure with User-Friendly Client-Management Software
- Perfect for Elevators, Schools, Hallways, Offices and Other Confined Spaces
- 100% Performance Guarantee
- One Year Limited Warranty

APPLICATIONS INCLUDE

IPC-13MP720EV



ELEVATORS



CLASSROOMS



STORAGE FACILITIES



OFFICE



HALLWAYS



PRISONS



HOSPITALS



CASINOS

SPECIFICATIONS

CAMERA TYPE	Sony 1/2.9" Color CMOS Sensor
RESOLUTION	Main Stream 1.3MP @ 30fps (1920 x 1080) Sub Stream 4CIF NTSC (704 x 480) PAL (704 x 576)
VIDEO FORMAT	NTSC / PAL
STANDARDS	ONVIF 2.0
CAMERA LENS TYPE	2.9mm Fixed MegaPixel Lens with 110° Viewing Angle
CAMERA S/N RATIO	>48dB
CAMERA SYNC / WHITE BALANCE	Automatic
CAMERA ELECTRONIC SHUTTER	1/50~1/10,000 Seconds
CAMERA MINIMUM ILLUMINATION	1.0 Lux
CAMERA IR CUT FILTER	Automatic / Mechanical
VIDEO COMPRESSION	H.264
PROTOCOL	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
DATA RATE	0.1Mbps~6Mbps
VIDEO CONNECTOR	BNC-Female @ 1 Volt P-P & RJ-45
COMMUNICATION PORT	RJ-45 (10/100Mbps Base-T Ethernet LAN) / 48VDC PoE IEEE 802.3af
POWER SUPPLY	Sold Separately - #PS-122C (12VDC Only) or #PS-4850PoE (PoE 48VDC Only)
POWER CONNECTOR	2.1mm Barrel (12VDC Only) & RJ45 (PoE 48VDC Only)
CAMERA CURRENT CONSUMPTION	130mA @ 12VDC
POE CURRENT CONSUMPTION	1.6 Watts @ 48VDC
CAMERA CONSTRUCTION	Rugged All-Weather IP-66 Rated Cast Aluminum Design
CAMERA DIMENSIONS	8" x 8" x 8" x 3" (203mm x 203mm x 203mm x 76mm)
CAMERA WEIGHT	1.1KG (2.5lbs)
OPERATING TEMPERATURE RANGE	-40°F to +170°F (-40°C to 77°C)
SOFTWARE	Multi-Camera CMS Included
NOTE	Add a Video Network Bridge to Make this Camera Wireless

Specifications are Subject to Change Without Notice

KIT INCLUDES

- IP CORNER MOUNT CAMERA
- 3FT CAT5 NETWORK CABLE
- DC POWER JACK CONNECTOR
- OWNER'S MANUAL
- CLIENT MANAGEMENT SOFTWARE (CD-ROM)
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY



1016C Sutton Drive, Unit 6, Burlington, ON Canada L7L 6B8
Tel: 905.336.9665 Fax: 905.336.9662 www.VideoTransmitters.com

VIDEO COMM
TECHNOLOGIES

© Copyright 2014 1156488 Ontario Inc.