

2MP Infrared IP Network Camera



NEW MAX 2 MegaPixel OPTICAL 5-50mm VARIFOCAL H.264 IP ONVIF IR RANGE 300 FEET IP-66

IPC-2MP1080IR - 2 Megapixel Color H.264 ONVIF IP All-Weather IR-300' Range 5-50mm Varifocal CMOS Camera

All New! This true HD 2 MegaPixel ONVIF 1080p Infrared IP Network Camera features an enhanced 5-50mm Varifocal lens with variable Infrared Night Vision up to 300 Feet. Perfect for all weather surveillance and monitoring applications with remote network access.



ADVANTAGES

- Easy to Install "Plug & Play"
- 2-MegaPixels @ 30fps (1920 x 1080) Streaming
- Varifocal IR Night Vision Array up to 300 Feet
- Enhanced Dynamic 5-50mm Optical Varifocal MegaPixel Lens
- Supports ONVIF Open IP Standards
- Rugged IP-66 Rated All-Weather Design
- Perfect for Protecting Property and Assets with Remote Network Access
- One Year Limited Warranty
- 100% Performance Guarantee

APPLICATIONS INCLUDE

IPC-2MP1080IR




CONSTRUCTION SITES



FREEWAY



HARBOR



BRIDGES



PARKING LOTS



AIRPORTS



INDUSTRIAL



MARINAS

SPECIFICATIONS

CAMERA TYPE	Micron 1/2.5" CMOS Sensor
RESOLUTION	Main Stream 2MP @ 30fps (1920 x 1080) Sub Stream 4CIF NTSC (704 x 480) PAL (704 x 576)
VIDEO FORMAT	H.264 NTSC / PAL
OPERATING SYSTEM	Linux
LENS TYPE	Enhanced Dynamic 5-50mm Varifocal Megapixel Lens with Day/Night IR-Cut Filter
IR RANGE	IR Array up to 300 Feet & 10,000+ Lifetime Hours (Made in Germany)
S/N RATIO	>60dB (Enhanced) with Automatic Sync / White Balance
PROTOCOL	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
DATA RATE	0.1Mbps~6Mbps
SYNC / WHITE BALANCE	Automatic
ELECTRONIC SHUTTER	1/50~1/10,000 Seconds
MINIMUM ILLUMINATION	Color 0.6 LUX / B&W 0.08 LUX ~ (0.0 LUX IR ON)
ETHERNET PORT	RJ-45 (10/100Mbps Base-T Ethernet LAN) / 48VDC PoE IEEE 802.3af Capable
VIDEO CONNECTOR	BNC-Female & RJ-45
POWER SUPPLY	12VDC - Model # PS-121C (Included) 48VDC PoE Injector - Model # PS-4810PoE (Sold Separately)
POWER CONNECTOR	2.1mm Barrel Jack & PoE RJ-45 Jack
CURRENT CONSUMPTION	150mA @ 12VDC (IR LEDs OFF) / 700mA @ 12VDC (IR LEDs ON) 50mA @ 48VDC (IR LEDs OFF) / 250mA @ 48VDC (IR LEDs ON)
CONSTRUCTION	Rugged All-Weather IP-66 Rated Powder-Coated Aluminum Design
DIMENSIONS	14" x 9" x 6" (364mm x 234mm x 147mm)
WEIGHT	1.7KG (3.7lbs)
OPERATING TEMPERATURE	-40°F to +170°F (-40°C to 77°C)
STANDARDS	Supports ONVIF Open IP Standards

Specifications are Subject to Change Without Notice

KIT INCLUDES

- 2 MEGAPIXEL IP NETWORK CAMERA
- CAMERA MOUNTING BRACKET
- 12VDC POWER SUPPLY
- OPERATING INSTRUCTIONS
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY



1016C Sutton Drive, Unit 6, Burlington, ON Canada L7L 6B8
Tel: 905.336.9665 Fax: 905.336.9662 www.VideoTransmitters.com

VIDEO COMM
TECHNOLOGIES

© Copyright 2014 1156488 Ontario Inc.