

2MP IR NETWORK BULLET CAMERA

PRO
SERIES



IPC-2MPSR300 - 2MP PRO-Series All Weather IR-300' Range 5-50mm Network Bullet Camera

PRO Series 2-MegaPixel ready, All-Weather Network Bullet Camera featuring an enhanced **5-50mm Varifocal zoom lens** with variable **infrared night vision up to 300 Feet**. Perfect for day & night surveillance applications including: Warehouses, Parking Lots, Shopping Centers, Gas Stations and other high-risk areas.



ADVANTAGES

- High-Definition H.264 **2-MegaPixels (1920 x 1080) @ 30fps**
- **High-Intensity Night-Vision IR Range up to 300 Feet**
- **Dynamic 5mm-50mm Varifocal Zoom Lens**
- Vandal-Resistant IP-66 Rated All-Weather Design
- ONVIF Compliant & PoE Ready for Easy Installation
- Includes License-Free 64 Channel Client Management Software
- Perfect for Warehouses, Parking Lots, Shopping Centers, Gas Stations and other High-Risk Areas
- 100% Performance Guarantee & World Class Technical Support

APPLICATIONS INCLUDE



PRO
SERIES

SPECIFICATIONS

| | |
|-----------------------------|---|
| CAMERA TYPE | 1/2.5" Micron CMOS Sensor |
| RESOLUTION | Main Stream 2MP @ 30fps (1920 x 1080) Sub Stream 4CIF NTSC (704 x 480) PAL (704 x 576) |
| VIDEO FORMAT | NTSC / PAL |
| STANDARDS | ONVIF |
| CAMERA LENS TYPE | 5-50mm Varifocal Zoom with 5.65°~53.2° Viewing Angle |
| CAMERA S/N RATIO | >60dB (Enhanced)) |
| CAMERA SYNC / WHITE BALANCE | Automatic |
| CAMERA ELECTRONIC SHUTTER | 1/50~1/10,000 Seconds |
| CAMERA IR RANGE | IR Array up to 300 Feet & 10,000+ Lifetime Hours (Made in Germany) |
| CAMERA MINIMUM ILLUMINATION | Color 0.6 Lux / B&W 0.08 Lux ~ (0.0 Lux IR ON) |
| CAMERA IR CUT FILTER | Automatic / Mechanical |
| VIDEO COMPRESSION | H.264 |
| PROTOCOL | TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP |
| DATA RATE | 0.1Mbps~6Mbps |
| VIDEO CONNECTOR | BNC-Female @ 1 Volt P-P & RJ-45 |
| COMMUNICATION PORT | RJ-45 @ 10/100Mbps Base-T Ethernet LAN and 48VDC PoE IEEE 802.3af |
| POWER SUPPLY | Sold Separately - #PS-122C (12VDC Only) or #PS-4850PoE (PoE 48VDC Only) |
| POWER CONNECTOR | 2.1mm Barrel (12VDC Only) & RJ45 (PoE 48VDC Only) |
| CAMERA CURRENT CONSUMPTION | 700mA @ 12VDC (IR ON) |
| POE CURRENT CONSUMPTION | 8.4 Watts @ 48VDC (IR ON) |
| CAMERA CONSTRUCTION | Rugged All-Weather IP-66 Rated Cast Aluminum Design |
| CAMERA DIMENSIONS | 14" x 9" x 6" (364mm x 234mm x 147mm) |
| CAMERA WEIGHT | 1.7KG (3.7lbs) |
| OPERATING TEMPERATURE RANGE | -40°F to +170°F (-40°C to 77°C) |
| SOFTWARE | Includes License-Free 64 Channel Client Management Software |
| NOTE | Add a Video Network Bridge to Make this Camera Wireless |



CMS INCLUDED

KIT INCLUDES

- NETWORK BULLET CAMERA
- MOUNTING BRACKET
- OWNER'S MANUAL
- CLIENT MANAGEMENT SOFTWARE
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY

