

## IP INFRARED BULLET CAMERA



### IPC-2MPSR80 -

2-MegaPixel H.264 ONVIF IP All-Weather IR-80' Range 2.8-12mm Remote Motorized Zoom & Focus Varifocal Bullet Camera

High-Performance 2-MegaPixel ONVIF + PoE ready, IP Network all-weather camera featuring a **2.8-12mm remote motorized varifocal zoom & focus** lens & dual high-intensity infrared night vision up to 80 Feet. Perfect for day & night surveillance applications including: Parking Lots, Shipping Yards, Storage Facilities, School Campuses, Warehouses & Construction Sites.



### ADVANTAGES

- Hi-Def H.264 2-MegaPixels (1920 x 1080) @ 30fps
- High-Intensity Dual IR Night-Vision LED Range Up to 80 Feet
- **2.8-12mm Remote Motorized Varifocal Zoom & Focus**
- Digital WDR, Back-Light Compensation, Digital Noise Reduction, Automatic Electronic Shutter & Auto Gain Control
- Vandal-Resistant IP-66 Rated All-Weather Design
- ONVIF Compliant & PoE Ready for Easy Installation
- Easy to Configure with User-Friendly Client-Management Software
- Perfect for Parking Lots, Shipping Yards, Storage Facilities, Malls, Warehouses & Construction Sites
- 100% Performance Guarantee
- One Year Limited Warranty

## APPLICATIONS INCLUDE

IPC-2MPSR80



SHIPPING YARDS



STORAGE FACILITIES



SCHOOL CAMPUS



PARKING LOTS

## SPECIFICATIONS

CAMERA TYPE	1/2.8" SONY Exmor IMX222 CMOS Sensor + 32-Bit Dual Core DSP
RESOLUTION	Main Stream 2MP @ 30fps (1920 x 1080) Sub Stream 4CIF NTSC (352 x 288) D1 (704 x 576)
VIDEO FORMAT	NTSC / PAL
STANDARDS	ONVIF
CAMERA LENS TYPE	2.8-12mm Remote Motorized Varifocal Zoom & Focus with 32° - 106° Viewing Angle
CAMERA S/N RATIO	>45dB + Dynamic Noise Reduction (DNR)
CAMERA SYNC / WHITE BALANCE	Automatic
CAMERA ELECTRONIC SHUTTER	1/50~1/100,000 Seconds
CAMERA IR RANGE	Dual High-Intensity IR LED Night-Vision up to 80 Feet
CAMERA MINIMUM ILLUMINATION	Color: 0.01 Lux / B&W 0.001 Lux
CAMERA IR CUT FILTER	Automatic / Mechanical
WDR FUNCTION	Digital Wide Dynamic Range
VIDEO COMPRESSION	H.264
PROTOCOL	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
DATA RATE	0.1Mbps~8Mbps
COMMUNICATION PORT	RJ-45 @ 10/100Mbps Base-T Ethernet LAN and 48VDC PoE IEEE 802.3af
POWER SUPPLY	Sold Separately Model #PS-4850PoE
POWER CONNECTOR	RJ-45 PoE + 2.1mm Barrel
CAMERA CURRENT CONSUMPTION	600mA @ 12VDC (IR ON)
POE CURRENT CONSUMPTION	8 Watts @ 48VDC (IR ON)
CAMERA CONSTRUCTION	Rugged All-Weather IP-66 Rated Cast Aluminum Design
CAMERA DIMENSIONS	6" x 3.2" x 3.2" (152mm x 81mm x 81mm)
CAMERA WEIGHT	972g (2.1Lbs)
OPERATING TEMPERATURE RANGE	-40°F to +170°F (-40°C to 77°C)
ON SCREEN DISPLAY MENU	Adjust Exposure, White Balance, Color, Sharpness, 4-Zone Motion Detection ON / OFF, 4-Zone Privacy Masking & Dead Pixel Compensation
SOFTWARE	Multi-Camera 64-Channel CMS Included
NOTE	Add a Video Network Bridge to Make this Camera Wireless

Specifications are Subject to Change Without Notice

## KIT INCLUDES

- IP BULLET CAMERA
- MOUNTING BRACKET
- 3FT CAT5 NETWORK CABLE
- DC POWER JACK CONNECTOR
- OWNER'S MANUAL
- CLIENT MANAGEMENT SOFTWARE (CD-ROM)
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY

