

speco technologies®

Four Wire Color Video Security Intercom System



VDP6000

Our two-way color video security intercom system has a flat 4" color screen. It offers a two way manual switcher, a 165 foot maximum wiring distance and can be used with an optional door release. A manual switcher allows the system to be expandable up to 2 monitors and 2 cameras. The system comes with an indoor/outdoor flush mount camera.

Specifications

	VDPM6F (Color Monitor)	VDPC6F (Flush Mount Color Camera)
Angle of Picture	N/A	Horizontal: 110° - Vertical 92°
Call Signal Device	Door chime	N/A
Communication System	Duplex handset	Duplex hands free conversation
Connection	Screw terminals	Screw terminals
Illumination	N/A	Infrared LEDs
Lens	N/A	2.9mm
Max Wiring Distance	165 ft. (22AWG wire)	165 ft. (22AWG wire)
Minimum Illumination	N/A	0.1 lux on object up to 19 feet
Monitor	4" Flat color CRT	N/A
Output Impedance	N/A	Video 300 ohm - Audio 600 Ohm
Scanning Frequency	Horizontal: 15.75 KHz, Vertical: 60Hz	Horizontal: 15.75 KHz, Vertical: 60Hz
Weight	2.86 lbs.	1.1 lbs.
Wiring	4 Wires, 22 gauge minimum	4 Wires, 22 gauge minimum
Housing	White plastic	Pewter gray metal
Operating Temp	14°F to 104°F	-4°F to 122°F
Power Consumption	Max 24V AC standby 2V AC	Max 3 watts
Power Source	12V regulated DC power supply included	Power supplied from monitor
Dimensions	8.25" H x 7.5" W x 2-1/3" D	7.25" H x 4.75" W x 3/4" D

Additional Outdoor Video Intercom System Components: (Sold Separately)

VDPM6F Extra Surface Mount Color Monitor (Dimensions: 8.25" D x 7.5" W x 2-1/3" H)

VDPC6F Extra Flush Mount Color Camera (Dimensions: 2" D x 4.75" W x 7.25" H)

VDPC6S Surface Mount Color Camera (Dimensions: 1.6" D x 3.5" W x 4.75" H)



VDPC6S

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880