clintonelectronics

CE-IDX20(B) Indoor D/N Dome Camera

















INFO:

- •1/3" SONY Super HAD II CCD
- •700 TVL Resolution
- •2.8~12mm (F1.2) Lens
- •NX4 Digital Signal Processor (DSP)
- •OSD Menu Control via Built-in Joystick, CE-REMOTE or CE-REMOTE-UTC
- 3 Axis Adjustment
- •DC12V/AC24V
- •Mounts to: Single Gang, Double Gang, 3-1/4" & 3-1/2", or 4" Oct/Rd Conduit Boxes
- •UL Listed

DIMENSIONS:





SPECIFICATIONS:

| CAMERA | CAMERA | |
|-----------------------|---|--|
| Image Sensor | 1/3" SONY Super HAD II CCD (960H) | |
| Resolution | 700 TVL | |
| Effective Pixels | 976 (H) x 494 (V) | |
| Scanning System | 2:1 Interlace | |
| S/N Ratio | 52dB (AGC Off) | |
| Sync System | Internal / Line Lock | |
| Minimum Illumination | 0.15 Lux (Color), 0.0006 Lux (Sens-Up) | |
| Shutter Speed | Auto / Manual (1/60, 1/50 ~ 1/100,000) | |
| Lens | 2.8-12mm (F1.2) Lens (D/N Version) | |
| Video Output | 1.0 Vp-p, 75 Ω | |
| Frequency | Horizontal: 15.734 KHz, Vertical: 59.94 Hz | |
| Power Consumption | Max. 220mA (DC12V), Max. 110mA (AC24V) | |
| Power Requirement | DC12V / AC24V | |
| Operating Temperature | 32°F -1 13°F / 0°C - 45°C | |
| Operating Humidity | 90% RH Max. | |
| Weather Rating | N/A | |
| IR LEDs | N/A | |
| Heaters/Fan | N/A | |
| Materials | Plastic Case w/Polycarbonate Dome | |
| Dimensions | 4.80" (Dia.) x 3.70" (H) / 121.9mm (Dia.) x 93.9mm(H) | |
| Weight | 0.60 lbs / 0.27 kg | |

| OSD | |
|-----------------------------|--|
| DSP Type | NX4 |
| Menu Control | OSD Menu Control via Built-In Joystick |
| Exposure | Brightness, Shutter, AGC |
| Sens-Up | Yes (Level Adjustable) |
| White Balance | ATW, AWB, AWC Set, Manual, Indoor, Outdoor |
| Digital Dynamic Range | Yes (DWDR) |
| Backlight Control | BLC, HSBLC |
| Day/Night | Auto, Color, B&W, External |
| Noise Reduction | 3DNR |
| Camera Title/ID | Yes (Up to 15 Characters) |
| Sync | Internal / Line Lock |
| Monitor | LCD, CRT |
| Motion Detection | 4 Areas |
| Privacy Masking | 8 Zones |
| Digital Image Stabilization | Yes |
| Dead Pixel Control | Yes (Defect) |
| Digital Effects | Mirror, Freeze, D-Zoom, Smart D-Zoom, Defog |
| Languages | English, Korean, Japanese, Chinese, Russian, Français, Español, Italiano, Português, Dutch, German, Polish, Turkish, Hebrew, Arab. |
| Other | Sharpness, Lens Shading |

| ACCESSORIES | |
|--------------------|---|
| CE-REMOTE | Plug in OSD remote |
| CE-REMOTE-UTC | Plug in Up The Coax OSD remote |
| CE-IDXWB (White) | Wall Bracket for IDX Series Cameras |
| CE-IDXPC (White) | Pendant Cap for IDX Series Cameras |
| CE-IDXDPC (White) | Deep Pendant Cap for IDX Series Cameras |
| CE-IDXWBB (Black) | Wall Bracket for IDX Series Cameras |
| CE-IDXPCB (Black) | Pendant Cap for IDX Series Cameras |
| CE-IDXDPCB (Black) | Deep Pendant Cap for IDX Series Cameras |

CERTIFICATIONS:







