



Link Eye

IP Analog Cameras



Model Name	KNC-VNNi101NHV15	KNC-VNWi101NHV15
PRODUCT PICTURE		
IP Rating	IP66 (Weather proof)	IP66 (Weather proof)
Image Device	1/3" Sony Super HAD CCD II	1/3" Sony Vertical Double-Density Interline CCD
Resolution	Max. 720 x 480 @ 30fps (NTSC), 720 x 576 @ 25fps (PAL) Min. 320 x 240 @ 30fps (NTSC), 320 x 288 @ 25fps (PAL)	Max. 720 x 480 @ 30fps (NTSC), 720 x 576 @ 25fps (PAL) Min. 320 x 240 @ 30fps (NTSC), 320 x 288 @ 25fps (PAL)
Lens	2.6 ~ 11mm / F1.2 DC Iris Vari-Focal Lens	2.6 ~ 11mm / F1.2 DC Iris Vari-Focal Lens
Day and Night	True Day & Night with ICR Mechanism	True Day & Night with ICR Mechanism
Min. Illumination	0.05 Lux / Faceplate, 0 Lux (IR LED on)	1.0 Lux / 30IRE@F2.0, 0.01 Lux (DSS), 0 Lux (IR LED on)
IR LEDs	30ea	30ea
Video Compression	MPEG4 SP@L3 (ISO/IEC 14496-2) / Motion JPEG	MPEG4 SP@L3 (ISO/IEC 14496-2) / Motion JPEG
Audio	Two-way, Full duplex External Microphone Input or Line Input (Selectable)	Two-way, Full duplex External Microphone Input or Line Input (Selectable)
Frame Rate	MPEG4 : 30/25 (NTSC/PAL) fps@D1 / Motion JPEG : 30/25 (NTSC/PAL) fps@D1	MPEG4 : 30/25 (NTSC/PAL) fps@D1 / Motion JPEG : 30/25 (NTSC/PAL) fps@D1
Video Streaming	•Simultaneous Motion JPEG and MPEG-4 •Controllable frame rate and bandwidth •Constant and variable bit rate (MPEG-4)	•Simultaneous Motion JPEG and MPEG-4 •Controllable frame rate and bandwidth •Constant and variable bit rate (MPEG-4)
Image Settings	•Compression levels: 100 (Motion JPEG) •Image rotation: 0, 180 degrees •Viewer Magnification: 0.5x, 1x, 1.5x, 2x •Overlay capabilities: time, date, text, privacy mask •De-interlace filter (Software)	•Compression levels: 100 (Motion JPEG) •Image rotation: 0, 180 degrees •Viewer Magnification: 0.5x, 1x, 1.5x, 2x •Overlay capabilities: time, date, text, privacy mask •De-interlace filter (Software)
Supported Protocols	IPv4, HTTP, HTTPS, TCP, RTSP, RTP, UDP, IGMP, RTCP, SMTP, FTP, ICMP, DHCP, ARP, DNS, DDNS	IPv4, HTTP, HTTPS, TCP, RTSP, RTP, UDP, IGMP, RTCP, SMTP, FTP, ICMP, DHCP, ARP, DNS, DDNS
Memory	RAM: 128MB, Flash: 32MB	RAM: 128MB, Flash: 32MB
Power	PoE Class 3 (IEEE 802.3af) DC12V: 600mA, AC24V: 630mA	PoE Class 3 (IEEE 802.3af) DC12V: 700mA, AC24V: 780mA
Operating Temperature	41°F~122°F (5°C~+50°C)	41°F~122°F (5°C~+50°C)

* Specifications & Features are subject to change without prior notice.

Website: www.ktncusa.com / www.ktncamerica.com

For details, contact us at (East: 201-393-0118 or sales-america@ktncamerica.com / West: 213-381-0061 or sales-usa@ktncusa.com)