



Vandal-proof Outdoor Dome Camera

IV-DV502V

Features:

- . 1/3" Sony Super HAD CCD
- . 560 TV Lines of Resolution
- . 2.8mm ~ 12mm DC Auto Iris Varifocal Lens
- . Day and Night Function
- . 0.3 Lux at F1.2 (Color)
- . 0.03 Lux (Black & White)
- . On Screen Display Menu
- . Motion Detection
- . Privacy Zone
- . Mirror
- . Service Video Output
- . 12Volt DC / 24 Volt AC Dual Voltage
- . IP 68



OSD CONTROL



SERVICE VIDEO OUT



SHOCK RESISTANT



SPECIFICATION	IV-DV502V
Resolution	560 TV Lines
Sensor	1/3 inch SONY Super HAD CCD
Lens	2.8mm ~ 12mm DC Auto Iris Varifocal Lens
Total Pixels	NTSC : 811(H) x 508(V) 410K Pixels
Effective Pixels	NTSC : 768(H) x 494(V) 380K Pixels
Scanning System	2:1 Interface
Synchronization	Internal
Frequency	NTSC : Horizontal: 15.734KHz / Vertical: 59.94Hz
Signal to Noise Ratio	More than 50 dB (AGC Off)
Video Output	CVBS : 1.0Vp-p / 75 Ohm
Minimum Illumination	0.3 Lux at F1.2 (Color) / 0.03 Lux (Black & White)
White Balance	ATW / ATC / Manual (2,100°K ~ 10,500°K)
Electronic Shutter Speed	Auto / Manual; NTSC : 1/60 second ~ 1/120,000 second
On Screen Display Menu	Built - in
Backlight Compensation	On / Off
Gain Control	On / Off
Day & Night	Auto / On
Motion Detection	On / Off; 64 Grids
Privacy Zone	On / Off; 4 Zones
Mirror	On / Off
Operating Temp / Humidity	-30° ~ 50° C / -22° ~ 122° F / 30% ~ 80% RH
Storage Temp / Humidity	-30° ~ 60° C / -22° ~ 140° F / 20% ~ 90% RH
Power	12 Volt DC / 24 Volt AC
Protection Rating	IP 68