



CCTV Dome Camera

IV-VZD207NL

Features:

- . High Sensitive 1/4" SONY Super HAD CCD
- . Built in Auto Focus / Auto Iris
- . 22x Optical Power Zoom Lens, 10x Digital Zoom (max. 220x)
- . Digital Slow Shutter
- . RS-485 Interface(Pelco-D)
- . OSD (On Screen Display), 3-Axis Lens Holder
- . DC 12V/AC 24V
- . Vandal Proof Dome Housing
- . Extra Video-out port for easier installation
- . Built-in Heater (Option)
- . IP 65



SPECIFICATION	IV-VZD207NL
Signal System	NTSC : 525 Lines
Scanning System	2:1 Interlace
Scanning Frequency (H)	15.734kHz
Scanning Frequency (V)	59.94Hz
Image Sensor	1/4 Inch Interline Transfer SONY Super HAD CCD
Total Pixels Number	811(H) x 508(V) 410K
Effective Pixels Number	768(H) x 494(V) 380K
Horizontal Resolution	480 TV Lines
Video Output Level	1.0 Vp-p (75 Ohms, composite)
S/N Ratio	More Than 48dB (AGC Off)
Digital Zoom Ratio	10x (Total Zoom Ratio : 220x), 2x ~ 10x Variable
Lens	22x Optical Zoom (F1.6, f=3.9~85.8mm) Video AF
Min. Illumination	Day(1.0 Lux), Night(0.001 Lux, DSS, Option)
Electronic Shutter Speed	1/60 ~ 1/10,000 Sec.
OSD Menu	On / Off
Sharpness Control	Manual (Up ~ Down)
Brightness Control	Manual (Up ~ Down)
White Balance	Auto / Push Auto
Input/Output Connector	Power : 2 Pin Terminal, Video Output : BNC
Supplied Voltage	DC 12V/AC 24V
Power Consumption	Max. 16.2W
Weight (Net)	Approx. 1.6kg