

## DAY / NIGHT BULLET CAMERA

 PRO  
SERIES


## CX-700SR105 700-Line Color All-Weather IR-105' Range 6mm - 22mm Varifocal CCD Camera

PRO-Series 700 Line, high resolution camera features a **6mm-22mm varifocal zoom lens** perfect for protecting property and assets with exceptional **night-vision ranging up to 105 Feet**.

## ADVANTAGES



- High Intensity **Night Vision Range up to 105'**
- **700 Line High-Resolution 960H Color CCD**
- **Dynamic 6mm-22mm Varifocal Lens** Perfect for Extreme Wide Angle Surveillance Applications
- External On-Screen Display Menu Control for Convenient Setup & Picture Adjustments
- Universal 3-Axis Mounting Bracket for Easy Installation and Camera Positioning
- Rugged All Weather IP-66 Rated Cast Aluminum Design with Sun-Shield Hood & Anti-Glare Lens
- Free Technical Support, Application Design Assistance & 100% Performance Guarantee

## APPLICATIONS INCLUDE

CX-700SR105




HARBOUR



PARKING LOTS



CONSTRUCTION SITES



FREEWAY

## SPECIFICATIONS

|                             |  |
|-----------------------------|--|
| VIDEO FORMAT                | NTSC   |
| CAMERA TYPE                 | 1/3 Sony 960H CCD Sensor   |
| RESOLUTION                  | 700 Lines  |
| CAMERA LENS TYPE            | 6mm-22mm Varifocal Lens  |
| CAMERA IR RANGE             | Up to 105 Feet   |
| CAMERA MINIMUM ILLUMINATION | 0.001 LUX @ F1.2   |
| CAMERA IR CUT FILTER        | Automatic / Mechanical   |
| WDR FUNCTION                | Zone Configurable Backlight Compensation   |
| CAMERA S/N RATIO            | >50dB  |
| CAMERA SYNC / WHITE BALANCE | Automatic  |
| VIDEO CONNECTOR             | BNC-Female   |
| VIDEO IMPEDANCE & LEVEL     | 75 Ohms @ 1 Volt P-P   |
| ON SCREEN DISPLAY MENU      | Adjust Exposure, White Balance, Color, Sharpness, Motion Detection ON / OFF, Privacy Masking, Monitor Mode & Dead Pixel Compensation |
| POWER SUPPLY INCLUDED       | Yes - Model #PS-121C Class V CEC   |
| CAMERA CURRENT CONSUMPTION  | 120mA @ 12VDC IR OFF / 600mA @ 12VDC IR ON   |
| CAMERA POWER CONNECTOR      | 2.1mm Barrel Jack  |
| CAMERA CONSTRUCTION         | Rugged All-Weather IP-66 Rated Cast Aluminum Design  |
| CAMERA DIMENSIONS           | 3.3" x 5.5" (84mm x 140mm)   |
| CAMERA WEIGHT               | 1.9Lbs (8061g)   |
| CAMERA MOUNTING BRACKET     | Integrated 3-Axis Cast Aluminum Wall-Mount   |
| OPERATING TEMPERATURE RANGE | -40°F to +170°F (-40°C to 77°C)  |

Specifications are Subject to Change Without Notice

## KIT INCLUDES

- ALL WEATHER IR CAMERA
- 12VDC POWER SUPPLY
- UNIVERSAL MOUNTING BRACKET
- OPERATING INSTRUCTIONS
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY

