clintonelectronics

CE-IDX70(B) Indoor True D/N WDR Dome Camera



















INFO:

- •1/3" SONY Super HAD II Double Scan CCD
- •800 TVL Resolution
- •2.8~12mm (F1.2) Lens (True D/N Version)
- Effio-V Digital Signal Processor (DSP)
- •OSD Menu Control via Built-in Joystick, CE-REMOTE or CE-REMOTE-UTC
- 3 Axis Adjustment
- •DC12V/AC24V
- •Mounts to: Single Gang, Double Gang, 3-1/4" & 3-1/2", or 4" Oct/Rd Conduit Boxes
- •UL Listed

DIMENSIONS:





SPECIFICATIONS:

CAMERA	
Image Sensor	1/3" SONY Super HAD II Double Scan CCD
Resolution	800 TVL
Effective Pixels	976 (H) x 494 (V)
Scanning System	2:1 Interlace (525 Lines)
S/N Ratio	>50dB (AGC Off)
Sync System	Internal
Minimum Illumination	Color: 0.1Lux (AGC ON); B/W: 0.001Lux (AGC ON)
Shutter Speed	1/60[s] ~ 1/100,000[s]
Lens	2.8-12mm (F1.2) Lens (True D/N Version)
Video Output	1.0 Vp-p, 75 Ω
Frequency	Horizontal: 15.734 KHz, Vertical: 59.94 Hz
Power Consumption	Max. 360mA (DC12V), Max. 240mA (AC24V)
Power Requirement	DC12V / AC24V
Operating Temperature	32°F -1 13°F / 0°C - 45°C
Operating Humidity	90% RH Max.
Weather Rating	N/A
IR LEDs	N/A
Heaters/Fan	N/A
Materials	Plastic Case w/Polycarbonate Dome
Dimensions	4.80" (Dia.) x 3.70" (H) / 121.9mm (Dia.) x 93.9mm(H)
Weight	0.60 lbs / 0.27 kg

OSD	
DSP Type	Effio-V
Menu Control	OSD Menu Control via Built-In Joystick or CE-REMOTE
Exposure	AGC (6dB ~ 44.8dB)
Sens-Up	Auto
White Balance	ATW: Indoor / Sunny / Shade (1,800°K ~ 10,500°K), Manual, Push, User 1/2, Push Lock
Digital Dynamic Range	WDR, ATR-EX
Backlight Control	BLC, HLC
Day/Night	Auto, Day, Night
Noise Reduction	2DNR / 3DNR
Camera Title/ID	Up to 26 Characters
Monitor	LCD / CRT
Motion Detection	4 Areas
Privacy Masking	15 Areas
Digital Image Stabilization	On/Off
Dead Pixel Control	Yes (White Pixel Mask)
Digital Effects	Flip, E-Zoom, Defog, IR Optimizer, Flk Less, Anti CR, Lens Shd Comp
Languages	English, Spanish, Russian, Portuguese, German, French, Japanese
Other	Brightness, Contrast, Sharpness, Hue, Color Gain

ACCESSORIES	
CE-REMOTE	Plug in OSD remote
CE-REMOTE-UTC	Plug in Up The Coax OSD remote
CE-IDXWB (White)	Wall Bracket for IDX Series Cameras
CE-IDXPC (White)	Pendant Cap for IDX Series Cameras
CE-IDXDPC (White)	Deep Pendant Cap for IDX Series Cameras
CE-IDXWBB (Black)	Wall Bracket for IDX Series Cameras
CE-IDXPCB (Black)	Pendant Cap for IDX Series Cameras
CE-IDXDPCB (Black)	Deep Pendant Cap for IDX Series Cameras

CERTIFICATIONS:







