



## LED-1561T

15" LED-backlit LCD monitor with built-in ATSC/QAM digital TV tuner has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations. For hotel applications, this model includes hotel TV functions, pro:idiom, and a MPI port for head-end connectivity.

### Benefits

- LED backlight: brighter picture using less power
- Displays native Full HD signals (1080i/p) with no downscaling
- True hospitality TV w/ pro:idiom chip and MPI port for head-end connectivity
- Hotel TV Functions: default input source, default TV channel, max volume, keypad lock, and cloning through USB
- Multiple input connections including HDMI and USB
- Built-in removable deskstand
- Built-in speakers

### Related Products

- LED-1561TL: Flush-mount version of LED-1561T
- LED-1561TR: Rack-mount version of LED-1561T

Specifications	
Mount	VESA 75 x 75mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	13.6" x 7.6" / 345.4 x 193.04mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	220 cd/m <sup>2</sup> (Nit)
Contrast Ratio	400:1
Back Light	LED (30K)
Dot Pitch	0.215(H) x 0.215(V)mm
Color Depth	16.7M
Number of Pixels	2,073,600
Response Time	8ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 5 Watts
Viewing Angle (L/R/T/B)	70/70/60/60 degrees
ATSC/QAM Digital Tuner	x1 RF Input
3D Comb Filter	Yes
Dimensions w/ Deskstand	14.8" x 10.8" x 5.5" / 375 x 275 x 140mm
Dimensions	14.8" x 9.8" x 1.9" / 375 x 248 x 48mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	Regulated 12VDC; 3A; Negative Ground
Power Consumption	30 Watts (Max)
HDMI	x1 Input
Composite	x1 RCA Input
MPI Port	x1 RJ-45 Input
USB	x1 Input
Audio	x1 RCA L/R Input / Output
Power	x1 2.1mm DC Input
Weight	Net: 2.6 lbs / 1.18 kg; Gross: 4.9 lbs / 2.2 kg

Specifications subject to change.