



LED-430x4-3GSDI

Functional and beautiful, this new generation model includes four LED-backlit, LCD monitors in a rack mount configuration. Each 4" monitor includes a native 3G-SDI input signal that is SMPTE 424M compliant, handling bit-rates of 2.97Gbit/sec which supports 1080p video up to 60 frames per second. This model is an ideal solution for broadcast studio environments that distribute and monitor VOD 1080p streams.

Benefits

- 3G/HD/SD-SDI Input and Output
- Quick access source buttons
- Wide viewing angle
- Up/Down tilting
- Tally function

Related Products

LED-500X3-3GSDI

Specifications

Mount	Rack (3RU)
HD Compatible	Yes
Case	Durable Metal
Native Aspect Ratio	16:9
Visible Screen Size	3.7" x 2.2" / 93 x 55.8mm
Resolution	800 x 480 dots
Brightness Rating	200 cd/m ² (Nit)
Contrast Ratio	400:1
Back Light	LED (15K)
Dot Pitch	0.116(H) x 0.116(V)
Colors	16.7 million
Response Time	20ms
Viewing Angle (L/R/T/B)	65/65/45/65 degrees
Dimensions	19" x 5.25" x 6.9" / 482.6 x 133.4 x 175.3mm
Operating Temperature	32 ~ 185°F / 0 ~ 85°C
Humidity	85% RH Max
Power Requirements	12VDC, 5A
Power Consumption	45 Watts (Max)
Component	x4 BNC (x3) Inputs
Composite	x4 BNC Inputs
S-Video	x4 BNC Inputs
VGA	x4 15-pin D-sub Inputs
HDMI	x1 Input
Tally Input	x1 9-pin D-sub Input
Power	x1 Screw-in DC Input
Weight	Net: 12.1 lbs / 5.5 kg; Gross: 14.8 lbs / 6.7 kg

Specifications subject to change.