



VertiLine166D **UL Listed CCTV Rack Mount Power Supply**

Rev. DSVertiLine166D_08052015



Overview

Vertiline166D CCTV Rack Mount Power Supply provides 16 PTC protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression. Vertiline CCTV Rack Mount Power Supplies are also available in eight (8) and twenty-four (24) output models with various power ratings.

Specifications

Input:

- Selectable 115VAC 60 Hz or 240VAC 50/60 Hz input.
 - 115VAC 60 Hz, 4 amp.
 - 240VAC 50/60 Hz, 2.5 amp.

Output:

- Sixteen (16) individually selectable 24VAC or 28VAC power outputs with OFF position.
- 24VAC or 28VAC @ 14 amp max. total (0.875 amp per device, 2.5 amp max.).
- Sixteen (16) PTC protected outputs rated @ 2.5 amp.
- Main fuse rated @ 15 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 172.0 BTU/Hr.
 - 28VAC: 200.63 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement:
115VAC: 460VA, 240VAC: 600VA.

Features:

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

Mechanical:

- Units can be rack, wall or shelf mounted.
- Modular 1U standard EIA 19" rack mount chassis.
- Enclosure Dimensions (H x W x D approx.):
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).
- Product weight (approx.): 15.4 lbs. (6.99 kg).
- Shipping weight (approx.): 16.7 lbs. (7.57 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



C-Tick Compliant - Z1409

Enclosure Dimensions (H x W x D approximate):
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)

