



LED-1708HDL

This LED-backlit flush monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

Related Products

- LED-1708HD
- LED-1708HDR
- LED-1908HD
- LED-1908HDL
- LED-1908HDR
- LED-1908HDVB
- LED-1908IP67
- LED-1908IP67TS

Specifications

Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	5:4
Visible Screen Size (WH)	13.4" x 10.7" / 340 x 272mm
Resolution	1280(H) x 1024(V)
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1
Back Light	LED (30K)
Dot Pitch	0.264(H) x 0.264(V)mm
Color Depth	16.7M
Number of Pixels	1,310,720
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 1.5 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
Digital Signal Processor	3D Comb Filter
Dimensions	16.9" x 15.1" x 2.9" / 427.8 x 381.5 x 72mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	DC 12V (AC100~240)[50/60]
Composite	x2 BNC Inputs / Outputs
VGA	x1 VGA 15-pin D-sub Input
HDMI	x1 Input
Audio	x1 L/R RCA Input; x1 3.5 PC stereo Input
Power	x1 2.1mm DC Input
Weight	Net: 11.4 lbs / 5.2 kg; Gross: 18.3 lbs / 8.3 kg

Specifications subject to change.