

LED-1908-IP67 - Front



LED-1908-IP67

This LED-backlit monitor is IP67 rated, which means it is dustproof and it will continue to function in a depth of one meter of water for at least 30 minutes. It features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals. This model is ideal for harsh environments that require a quality picture display.

Benefits

- Displays 1080i/p digital video
- Waterproof, IP-67 rated
- 3D Comb Filter for better picture quality
- Analog video is very clear with no detail loss
- High contrast ratio for better picture definition
- Durable sealed metal case

Related Products

- LED-1908HDL - 19" LED backlit Flush mount monitor
- LED-1908HDR - 19" LED backlit Rack mount monitor
- LED-1908HD - 19" LED backlit Standalone monitor
- LED-1908HDB - 19" LED backlit high brightness monitor
- LED-1908-IP67TS - 19" LED IP-67 rated, touch screen Wall mount monitor
- LED-1708HD - 17" LED backlit Standalone monitor
- LED-1708HDL - 17" LED backlit Flush mount monitor
- LED-1708HDR - 17" LED backlit Rack mount monitor

Optional Accessories

- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable
- WMC-2342 Ceiling mount bracket for 1.5" NPT pipe (order with WM-31)

Specifications

Mount	Wall: VESA 100mm x 100mm
HD Compatible	Yes
Anti Glare Coating	Yes
Selectable Color Temp.	Yes
Case	Durable Metal
IR Remote Control	No
Native Aspect Ratio	5:4
Visible Screen Size (WH)	376.3 x 301mm / 14.8" x 11.8"
Resolution	1280(H) x 1024(V)
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1 (dynamic)
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.294(H) x 0.294(V)
Color Depth	16.7 M
Number of Pixels	1,310,720
Response Time	5 ms
Viewing Angle (L/R/T/B)	80/80/65/65 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Composite Video	1 Input
PC	1 VGA input
HDMI	1 Input
Power	1 DC input
Power Requirements	DC 12V (AC100~240)[50/60]
Power Consumption	15W Max
Dimensions	442 x 362.9 x 55.5mm/17.4" x 14.3" x 2.2"
Operating Temp/Humidity	32 ~ 113°F / 0 ~ 45°C, 10% ~ 100% humidity
Weight	Net 7.3Kgs/16 lbs, Gross 11.9Kg/26.25 lbs

LED-1908-IP67 - Back

