PLASMA TV

Plasma Widescreen Commercial HDTV



BUILT-IN TUNERS ATSC/NTSC/QAM Clear

PUBLIC DISPLAY SETTINGS Cloneable with TVLink-Loader

NATIVE DISPLAY RESOLUTION 1366 x 768

> CONTRAST RATIO 7,000:1

HIGH BRIGHTNESS $1,200 \text{ cd/m}^2$

2 HDMITM INPUTS WITH HDCP

LG'S EXCLUSIVE XD ENGINE™

2 YEAR LIMITED WARRANTY (parts/labor)






SHARPER BRIGHTER CLEARER

ULTRA CONTRAST


AT A BLAZINGLY FAST 370 MILLION PIXELS PER SECOND, THE PROCESSOR USES A HISTOGRAM ANALYZATION TOOL TO CLARIFY THE IMAGE DATA ACCORDING TO SIGNAL BRIGHTNESS LEVELS.



Dramatization

DYNAMIC BLACK STRETCH

THE MINIMUM BLACK LEVEL OF AN IMAGE IS AUTOMATICALLY DETECTED AND ADJUSTED ACCORDING TO BRIGHTNESS.



Dramatization


ACCESSORIES

TLL-1100A TVLink-Loader

By using the handheld, rechargeable TVLink-Loader, the installer can "clone" the Public Display Settings from one TV and then transfer this information quickly to many other TVs that have this feature.



FEATURE



PUBLIC DISPLAY SETTINGS CLONING CAPABLE WITH TVLink-Loader


When used in public areas, these HDTVs can be easily programmed by the installer to have the TV turn on at a specified channel/volume level, set the minimum/maximum volume, lock out the control panel/remote, set the aspect ratio, and return to a factory reset. By using Power Management, these displays can be programmed to turn off if there has been no activity (remote or control panel buttons) for a preset time (1-7) hours.

PWMT300

FIXED OR TILTING WALL MOUNT

- Fits most LG 23" to 60" flat panel screens
- Easily expandable adapter brackets and wall plate
- Adjustable tilt of +15°/-5° for viewing flexibility
- Intuitive design for easy installation
- Security and standard screws included
- Portrait/landscape capability with mounting hole patterns up to 41"(W) and 26.37" H
- For mounting to wood studs, solid concrete, or cinder block only






The PWMT300 is a Peerless® mount that is available for order at LG Electronics USA, Inc.


CLEAR SCREEN

USING THE NOISE FILTER INSIDE THE XD ENGINE CHIP, THE IMAGE IS ANALYZED FOR TEMPORAL AND SPATIAL INFORMATION TO REDUCE MPEG NOISE.




ADVANCED VIVID COLOR

COLORS THAT ARE SENSITIVE TO THE HUMAN EYE ARE OPTIMIZED TO THE NEAREST TRUE COLOR BY THE SELECTIVE COLOR CONTROL.



INTELLIGENT EDGE CONTROL

EDGE LINES ARE EMPHASIZED BY IMPROVING THE TRANSITION FROM THE BACKGROUND TO THE MAIN OBJECT.





Dramatization

DIMENSIONS


REMOTE CONTROL







REAR JACK PACK PANEL



SIDE JACK PACK PANEL



PDP Panel Type	60"
Display Area	59.5" diagonal
Native Display Resolution	1366 × 768
Contrast Ratio	7,000:1
Brightness	1,200 cd/m ²
Fluid Motion (180Hz Effect)	Yes, Ensures a smoother cleaner picture
_	60,000 hours to Half Brightness
Life Span (approx.)	Glass Filter
High Contrast Screen w/Non-Glare Coating	Glass Filler
·	Over 160°
Viewing Angle (H/V) VIDEO	Over 100
ATSC/NTSC/QAMClear Tuners	Built-in
	3D Y/C
Digital Comb Filter	4 Modes
Color Temperature Adjustment	
3:2 Pulldown Cinema Correction	480i Only
Aspect Ratio Adjustment	6 Modes
EZ Video/Picture Selection Modes	5 Modes
XD Engine	Yes
Black Stretcher (Black Level Enhancer)	Yes
DTV Signal Strength Indicator	Yes
Displayable Colors	1.07 Billion
Image Sticking Minimization	White Wash, Pixel Orbiter, Inversion
Decoder Format	MPEG-2
Pixel Pitch	966µm (H) × 966µm (V)
DLTI (Digital Luminance Transient Improver)	Yes
DCTI (Digital Color Transient Improver)	Yes
REAR INPUTS	
Antenna/Cable In (RF)	1
HDMI with HDCP (DVI with Adapter)	2
Composite Video & Audio L/R In	1
S-Video In	1
Component HD/DVD & Audio L/R In	2
RGB In (PC/DTV Input)	1
Audio In (RGB/DVI with Adapter)	1
RS-232C In (Control/Service)	1
Remote Control In (IR)	1
USB	1 (Service)
REAR OUTPUTS	·
Composite Video & Audio L/R Out	1
Digital Audio Out (Optical)	1
SIDE INPUTS	
Composite Video & Audio L/R In	1
S-Video In	1
UPC	7 9192 17256 2
AUDIO	<u> </u>
Audio Output Power	20W (10W × 2)
Speaker System Details	2 Way 4 Speaker
Surround System Type	SRS TruSurrount XT®
Mono/MTS Stereo/SAP	Yes
EZ Sound/Sound Selection Mode	6 Modes
Mute	Yes
	Yes
EZ SoundRite (Auto Volume Levelor)	Yes
Dass /Troble /Dalan	
Bass/Treble/Balance 3D EchoSound System	Yes

SPECIAL FEATURES	
Custom Input Labels	Yes
Trilingual Menus	English, Spanish, French
EZ Menus (High Performance Interface)	Yes
EZ Scan (Auto Channel Programming)	Yes
Favorite Channel Selection/Surf	Yes
Flashback (Previous Channel)	Yes
Closed Caption	Yes
Intelligent Fan Control	Yes
Parental Control w/V-Chip	Yes
On / Off Timer	Yes
Sleep Timer	Yes (10 min. to 240 min.)
Auto Off (When no video is present)	Yes (After 10 minutes)
Auto Clock/Manual Clock	Yes
Auto Input Detect	Yes
Channel Block	Yes
Discrete IR Codes	Yes
1080p Source Input	Yes
CABINET	
Cabinet Style	Table Top
Table Stand Included	Yes
Cabinet Color	Black
Stand Color	Black
Dimensions with Stand (W × H × D)	60.8" × 40.8" × 16.1"
Without Stand (W × H × D)	60.8" × 38.5" × 4.7"
Packaging (W × H × D)	67.2" × 45.7" × 20.3"
Weight w/Stand	163.1 lbs (73.9 Kg)
Weight w/o Stand	137.3 lbs (62.3 Kg)
Weight with packaging	189.2 lbs (85.8 Kg)
VESA TM Compatible	600mm × 400mm, M8 Screw
OPERATING ENVIRONMENTS	ooonini ~ 400nini, M6 Sciew
	-4°F to 140°F (-20°C to 60°C)
Storage Temperature Range	under 85%
Storage Humidity Range	
Altitude	under 2,000m (under 6,561 ft.)
Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Humidity Range	under 80%
REQUIRED LISTING	V
UL, c-UL, FCC	Yes
RoHS Compliant	Yes
SERVICE/LIMITED WARRANTY	2 Years Parts/Labor
ACCESSORIES	
Supplied accessories	Owners Manual
	Power Cord (6 foot)
	LG Universal Remote Control
	75Ω Round Cable (10 foot)
COMPATIBLE FORMATS	
HDTV, NTSC, VGA, SVGA, XGA	Yes
Maximum Computer Resolution (RGB)	1366 × 768
POWER	
Power Consumption	700 Watts / 3 Watts in Standby
Power Source	AC 100 - 240V ~ 50 / 60 Hz
ENERGY STAR® Compliant	Yes

www.LGcommercial.com



LG Electronics U.S.A., Inc. Commercial Products Division 2000 Millbrook Drive, Lincolnshire, IL 60069

Customer Service: 888.865.3026

Contact your LG Regional Sales Representative: B2B: 800.897.8788

Hospitality: 800.228.1236

Channel Markets: 800.897.8871

SPEC_60PC1DC LG070818_PR







All screen images are simulated. Dimensions and weights are approximate. Design, features and specifications subject to change without notice.

© Copyright 2008 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp. Dual XD Engine is a trademark of LG Electronics USA, Inc.

HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. VESA is a trademark of Video Electronics Standards Association. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Peerless is a registered trademark of Peerless Industries, Inc. All other product and brand names are trademarks or registered trademarks of their respective companies. TruSurround XT and SRS are trademarks of SRS Labs, Inc.



Printed in the USA. July 2008