

LIGHT COMMERCIAL STRIKES

FEATURES

- **Durability - 300,000 Life Cycles**
- Holding Force - 1200 lbs
- Solid Brass Locking System
- Cast Steel Latch
- Heavy Duty Latch Spring
- Solenoid Actuated

<u>Voltage</u>	<u>Current/Amps</u>	<u>Ohms</u>	<u>Sound</u>	<u>Duty</u>
10-16VAC	0.60 - 0.90	10.0	Buzz	Intm
12VDC	0.50 - 1.00	10.0	Silent	Intm
24VAC	0.42	47.0	Buzz	Intm
24VDC	0.20	119.0	Silent	Intm



012

For new or replacement installations in metal jambs. Use with locksets having **up to 5/8" throw**, based on 1/8" door gap.

Face Plate 4-7/8" x 1-1/4" – Mortise Backset 1-5/8" – Cavity Depth 9/16"
– Cavity Width 9/16" – Cavity Height 1-1/2"



S012

For new or replacement installations in metal jambs. Use with locksets having **up to 3/4" throw**, based on 1/8" door gap.

Face Plate 4-7/8" x 1-1/4" – Mortise Backset 1-5/8" – Cavity Depth 5/8" –
Cavity Width 3/4" – Cavity Height 1-1/2"

FEATURES

- Miniature Design
- Die Cast Case
- Solid Cast Latch - Chrome Plated
- Non Handed
- Heavy Duty Latch Spring

<u>Voltage</u>	<u>Current/Amps</u>	<u>Ohms</u>	<u>Sound</u>	<u>Duty</u>
10-16VAC	0.82 - 1.44	6.8	Buzz	Intm
12VDC	0.184	65.0	Silent	Intm
24VAC	0.895	14.0	Buzz	Intm
24VDC	0.100	240.0	Silent	Intm



014

For new or replacement installations in metal jambs. Use with locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 2-3/4" x 1-1/8" – Mortise Backset 1-1/4" – Cavity Depth 1/2" –
Cavity Width 5/8" – Cavity Height 1-1/8"



014W

For new or replacement installations in wood jambs. Use with locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 4-7/8" x 1-1/4" – Mortise Backset 1-5/8" – Cavity Depth 9/16"
– Cavity Width 9/16" – Cavity Height 1-1/2"