



## GVYI.R18465

## Gasketing and Edge-sealing Materials for Fire Doors, Positive-pressure Tested

[Page Bottom](#)

## Gasketing and Edge-sealing Materials for Fire Doors, Positive-pressure Tested

[See General Information for Gasketing and Edge-sealing Materials for Fire Doors, Positive-pressure Tested](#)

## ZERO INTERNATIONAL INC

R18465

415 CONCORD AVE  
BRONX, NY 10455-4801 USA

Door Bottom, Models 111, 153, 253, 381, all Category G Gaskets for use with Listed steel frames and/or Classified steel-covered composite, hollow-metal doors rated up to 3 h, wood and plastic-covered composite doors rated up to 1-1/2 h, and wood core doors rated 20 min. Also suitable as Category J Gaskets for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to 3 hrs; and wood and plastic covered composite doors rated up to 1-1/2 hrs.

Door Bottom Gasketing, Models 58FS, 253FS, 320A, 321AA, 323A, 339FS, 350A, 351A, 352A, 354A, 355A, 360A, 361A, 364A, 364FS, 365A, 365FS, 367A, 368, 369A, all Category J Gaskets for use with Listed steel frames and/or Classified steel-covered composite, hollow-metal doors rated up to 3 h, wood and plastic-covered composite doors rated up to 1-1/2 h, and wood core doors rated 20 min.

Door Sweep, Models 329, 39, 339, 50M, 8191, 8197, 571, 8194, all Category G Gaskets for use with Listed steel frames and/or Classified steel-covered composite, hollow-metal doors rated up to 3 h, wood and plastic-covered composite doors rated up to 1-1/2 h, and wood core doors rated 20 min. Also suitable as Category J Gaskets for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to 3 hrs; and wood and plastic covered composite doors rated up to 1-1/2 hrs.

Frame kerf system, Models 820, FS821 with FS3003, Category G Edge Sealing System for use with Category B wood core doors rated 20 minute fire tested without hose stream. Also suitable as a Category J Gasket for use with wood and plastic covered composite doors rated up to 1-1/2 hrs.

Frame applied stop systems, Models 770, 7770, with FS1001, made of aluminum are Category G Edge Sealing Systems for use with Category B wood core doors rated for 20 minutes.

Frame applied stop system, Models 770ST, 7770ST, manufactured from steel with FS1001 Category G Edge Sealing System for use with Category B wood and plastic covered composite doors rated up to 1-1/2 hrs. Also suitable as Category J Gaskets for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to 1 1/2 hrs and wood and plastic covered composite doors rated up to 1-1/2 hrs.

Frame applied stop system, Model 837 Category G Edge Sealing System for use with Category B wood core doors rated 20 minute fire tested without hose stream. Also suitable as a Category J Gasket for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to 1 1/2 hrs and wood and plastic covered composite doors rated up to 1-1/2 hrs.

Jamb-up perimeter seal, Models 312, 318, 322, 328, 475, 485, 8302, 8303, 8877, 8878, Category H Edge Sealing System for use with Category B wood cored doors rated 20 minute fire tested without hose stream, Category B wood and plastic covered composite doors rated up to 1-1/2 hrs, and steel covered composite and hollow metal type fire doors rated up to 3 hrs: Also rated as a Category J gasket for use with Listed steel frames.

Meeting style, Models 59FS, 55FS/555FS, 159FS, 555A, 557FS/56FS, 3056FS, 3557FS, 56(+)/557(+), 55(+)/555(+), 56FS(+)/557FS(+), 55FS(+)/555FS(+), all with FS1001, Category G Edge Sealing System for use with Category B wood core doors rated 20 minute fire tested without hose stream. Also suitable as Category J Gaskets for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to 3 hrs; and wood and plastic covered composite doors rated up to 1-1/2 hrs.

Meeting edge protection, Model 59FS with FS3003 Category G Edge Sealing System for use on Category B wood core doors rated 20 minutes.

Perimeter, Models 58FS, 140FS, 253FS, 302FS, 328FS, 770A, 770FS, 33(+), 100(+), 873(+), 8306, 326, 477, 870, 712, 570, 31, 99, 429, all with FS1001, Category G Edge Sealing System for use with and Category B wood core doors rated 20 minute fire tested without hose streams. Also suitable as Category J Gaskets for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to 3 hrs; and wood and plastic covered composite doors rated up to 1-1/2 hrs.

Self-adhesive perimeter seal, Models 188S, 188FS, 488S, 8042S and 8144S Category H Edge Sealing System for use with Category B wood cored doors rated 20 minute fire tested without hose stream, Category B wood and plastic covered composite doors rated up to 1-1/2 hrs. and steel covered composite and hollow metal type fire doors rated up to 3 hrs. Also rated as a Category J gasket for use with Listed steel frames.

Self-adhesive perimeter seal, Models 188S, 188FS, and 8144S Category G/Category H Edge Seal/Smoke Seal and Draft Control Gasket for use with Category B wood and wood type or plastic covered composite type fire doors rated up to and including 1/3 hr. Also suitable as a Category J gasket for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to and including 3 hrs; wood and plastic covered composite doors rated up to and including 1-1/2 hrs.

Self-adhesive perimeter seal, Models 117S, 8145S, 8150, 8216S, and 8217S Category J Gaskets for use with Listed steel frames and/or Classified steel covered composite, hollow metal doors rated up to and including 3 hrs; wood and plastic covered composite doors rated up to and including 1-1/2 hrs.

Self-adhesive perimeter seal, Model 188FS-S Category G Edge Seal for use with Cat. B wood composite covered type fire doors rated up to