

VESDA-E VEU



The VEU series of aspirating smoke detectors are the premium detector of the VESDA-E range. An Ultra-wide sensitivity range; 15 times greater than VESDA VLP, and provision for more sampling holes provide an increased coverage in high airflow applications by up to 40%. Considerably longer linear pipe runs and extended branched pipe network configurations cater perfectly to applications with higher ceilings providing an increased coverage by up to 80% whilst allowing convenient detector mounting for ease of service and maintenance. A range of revolutionary new features provide unsurpassed detection performance, flexibility, field programmability, connectivity and reduced total cost of ownership.

Installation, Commissioning and Operation

VEU features a robust IP40-rated enclosure and is equipped with a powerful aspirator that provides a total pipe length of 800 m (2,624 ft). It is fully supported by the ASPIRE-E and Xtralis VSC software applications which facilitate ease of pipe network design, system commissioning and maintenance together with compatibility with existing VESDA installations.

Color touch screen display

The VEU-A10 detector features a 3.5" colour touch screen display which provides a range of status information including smoke level as well as trouble conditions. A simple navigation system allows the user to view all the status information.

VESDAnet™

VESDA devices communicate on VESDAnet which provides a robust bi-directional communication network allowing continued redundant operation even during single point wiring failures. VESDAnet enables primary reporting, centralized configuration, control, maintenance and monitoring.

Ethernet and WiFi connectivity

VESDA-E detectors offer Ethernet and WiFi connectivity as standard features. The detector can be added to a corporate network, allowing WiFi enabled tablet devices and laptops installed with Xtralis configuration software to connect wirelessly to the detector via the network.

Backward Compatibility

VESDA-E detectors occupy the same mounting footprint, pipe, conduit and electrical connector positioning as VESDA VLP and VLS detectors hence providing complete backwards compatibility.

VEU-A00, VEU-A10

Features

- Short wavelength laser based detection
- Inherent absolute calibration
- Advanced detection technology equivalent to hundreds of thousands of sensors
- Clean air barrier for optics protection
- Most robust contamination resistance
- Ultra-wide sensitivity range
- Flow fault thresholds configurable per port
- Long-life, easy-to-replace filter
- Quiet operation
- LEDs for alarm and fault signalling
- 3.5" colour touch screen for status review
- Advanced remote diagnostics
- Area coverage up to 2,000 m² (21,500 ft²)
- Up to four inlet pipes
- Total pipe length of 800 m (2,624 ft)
- Referencing
- AutoLearn™ Smoke and Flow
- Seven programmable relays
- Two GPIs, monitored and unmonitored
- Ultrasonic flow sensing
- Xtralis VSC, VSM4 and ASPIRE-E PC software support
- IP 40 enclosure (not UL tested)
- Easy mounting with optional steel support bracket
- Field replaceable aspirator, sampling module, filter and detection chamber
- VESDAnet networking
- Ethernet 100 base T
- WiFi, 802.11 b/g/n
- Local host-mode USB port
- Easy cable termination access
- Event Log (20,000 events)

Listings / Approvals

- UL
- ULC
- VdS
- CE
- ActivFire
- EN 54-20, ISO 7240-20
 - Class C (100 holes / Fire 1 = 0.062% obs/m)
 - Class B (80 holes / Fire 1 = 0.026% obs/m)
 - Class A (80 holes / Fire 1 = 0.015% obs/m)

Classification of any configuration is determined using ASPIRE-E.

Regional approvals listings and regulatory compliance vary between product models. Refer to www.xtralis.com for the latest product approvals matrix.

VESDA-E VEU

VEU-A00, VEU-A10

Specifications

Supply voltage: 18-30 VDC (24 V Nominal)

Power consumption @ 24VDC:

	VEU-A00			VEU-A10		
Aspirator Setting	1	5	10	1	5	10
Power (Quiescent)	7.0 W	8.8 W	14.7 W	8.2 W	10.0 W	15.8 W
Power (In Alarm)	7.8 W	9.6 W	15.5 W	10.4 W	11.6 W	16.6 W

Dimensions (WHD):	350 mm x 225 mm x 135 mm (13.8 in x 8.9 in x 5.3 in)
Weight:	VEU-A00 - 4.800 kg (10 lbs 9 oz) VEU-A10 - 4.835 kg (10 lbs 10 oz)
Operating conditions:	Ambient: 0°C to 39°C (32°F to 102°F) Sampled Air: -20°C to 60°C (-4°F to 140°F) Tested to: -20°C to 55°C (-4°F to 131°F) Humidity: 10% to 95% RH, non-condensing
Sampling network:	Maximum area of Coverage: 2,000 m ² (21,500 sq.ft) Minimum airflow per pipe: 15 l/m
Maximum pipe lengths:	Total Pipe Length (with branches): 800 m (2624 ft) Maximum length per pipe, when using four straight pipes: 100 m (328 ft)
Computer design tool:	ASPIRE-E™
Pipe:	Inlet: External diameter 25 mm or 1.05 in (3/4 in IPS) Exhaust: External diameter 25mm or 1.05 in (3/4 in IPS) via adaptor
Relays:	7 programmable relays (latch or non-latch states) Contacts rated 2 A @ 30 VDC (Resistive)
IP rating:	IP40
Cable access:	4 x 26 mm (1.02 in) cable entries
Cable termination:	Screw Terminal blocks 0.2–2.5 sq mm (30–12 AWG)
Dynamic Range:	0.0002%/m (0.00006% obs/ft) to 20% obs/m (6.25% obs/ft)
Sensitivity Range:	0.001% - 20.0% obs/m (0.0003 to 6.25% obs/ft)
Threshold setting range:	Alert: 0.001%-2.0% obs/m (0.0003%-0.625% obs/ft) Action: 0.001%-2.0% obs/m (0.0003%-0.625% obs/ft) Fire1: 0.001%-2.0% obs/m (0.0003%-0.625% obs/ft) Fire2: 0.001%-20.0% obs/m (0.0003%-6.25% obs/ft)
Software features:	Event log: Up to 20,000 events stored in FIFO format, smoke level, user actions, alarms and faults with time and date stamp AutoLearn: Min 15 minutes, Max 15 days. Recommended minimum 1 day. While AutoLearn is in progress, thresholds are NOT changed from pre-set values.

How it works

Air is continually drawn from the protected area through the air sampling pipe network and into the detector by a high efficiency aspirator. The air sampling pipe network can contain up to four pipes.

The air from each sampling pipe passes through an airflow sensor and then a sample of the air is drawn into the smoke detection chamber via the sampling module, after first passing through the filter. An additional filter provides clean air to protect the optical surfaces inside the detection chamber from contamination.

The Flair™ detection chamber uses the equivalent of 330,000 sensors and sophisticated algorithms for detection and particle classification.

If the detected smoke is higher than the set alarm thresholds it is reported as an Alert, Action, Fire1 or Fire2 alarm condition.

Air is exhausted from the detector and may be vented back into the protected area.

Alarms can be signalled via Relays and VESDAnet. Ethernet and WiFi can be used for configuration and secondary monitoring, and a USB interface is provided for initial setup.

A series of LEDs display Alarm, Trouble, Disable and detector power on status. A button allows the user to Reset or Disable the detector. In addition, an optional 3.5" LCD displays detector status including smoke level and a smoke level bar graph, alarm thresholds, trouble status, % airflow level, normalization status and filter life used.

Ordering Information

VESDA-E VEU with LED's	VEU-A00
VESDA-E VEU with 3.5" Display	VEU-A10
Mounting bracket (optional)	VSP-960

Spare Parts

VESDA-E Exhaust adaptor US	VSP-961
VESDA-E Filter	VSP-962
VESDA-E Filter - 20 pieces	VSP-962-20
VESDA-E Aspirator	VSP-963
VESDA-E Smoke Detection Chamber	VSP-964
VESDA-E Sampling Module	VSP-965

Approvals Compliance

Please refer to the Product Guide for details regarding compliant design, installation and commissioning.

www.xtralis.com

UK and Europe +44 1442 242 330 D-A-CH +49 431 23284 1 The Americas +1 781 740 2223

Middle East +962 6 588 5622 Asia +86 21 5240 0077 Australia and New Zealand +61 3 9936 7000

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

Xtralis, Xtralis logo, The Sooner You Know, VESDA, ICAM, ECO, OSID, HeiTel, ADPRO, IntrusionTrace, and LoiterTrace are trademarks and/or registered trademarks of Xtralis and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label.

This document is subject to copyright owned by Xtralis. You agree not to copy, communicate to the public, adapt, distribute, transfer, sell, modify or publish any contents of this document without the express prior written consent of Xtralis.

Doc. no. 22065_08

Part: 30278

