

## mortise cylinders -

fixed core for obsolete products


The following fixed core cylinders are available for obsolete Yale® mortise products.

NA1 -1 #	Decarintian	5-Pin	Lengths		
Model #	Description		6-Pin	7-Pin	Cam
1152	Standard cylinder for obsolete cast iron mortise locks	1" (25)	1-1/8" (29) 1-1/2" (38) 1-1/4" (32) 1-5/8" (41) 1-3/8" (35) 1-3/4" (44)	1-1/4" (32) 1-5/8" (41) 1-3/8" (35) 1-3/4" (44) 1-1/2" (38)	1161
1719*	Standard cylinder for obsolete Hotel/Motel cast iron locks		1-3/8" (35)		1160
5152	Security cylinder for obsolete cast iron mortise locks		1-1/8" (29) 1-1/4" (32)	1-1/4" (32)	1161
U5152	High security cylinder for obsolete cast iron mortise locks		1-1/8" (29) 1-1/4" (32)	1-1/4" (32)	1161


<sup>\*</sup>Cylinders are 6-pin for master keying expansion purposes. Locksets and housings will be 7-pin in length to accommodate top level master keys. See page 6 for more information.

dimensions


#### **Standard Cylinders**




#### **Security Cylinders**



#### **Thumbturn Cylinders**



#### **High Security Cylinders**



#### Dimensions are shown in inches (millimeters)



# cylinders and keying manual

### cams —

	Model No.	Description	Application		Model No.	Description	Application
.742"	2160	Std for 2123, 2153, S2053, 2719, 5153, U5153, 5719, 2196, 2197, 2196H, 5196, 5197, 5196H	Steel case mortise or auxiliary locks, exit device alarms and cylinder dogging for 7000 series exit devices.	E .640"	1161E	Opt for 1194, Std for 2153 when used for 2100 cylinder dogging	Obsolete cast iron mortise locks, cylinder dogging for 2100 series exit devices.
.500"	2130	Std for 2123S, 2153S, S2053S, 2196S, 2197S, 5196S, 5197S	Steel case mortise locks, inside operation for 8817-2 and 8834-2 functions.	R.750"	1161G	Opt for 1194, 1194H, 5194, 5194H	Keyswitches.
.780"	1160	Std for 1153, S1053H, 1719, 5719, U5719	Obsolete 310 series deadlocks,	.550"	1161L	Opt for 1123, 1152, S1052H, 5152, U5152	Adams Rite MS 1800 series locks and 4700 series latches.
.730"	1160E	Std for 1194, 1194H, 5194, 5194H	Obsolete cast iron mortise locks.	<b>R</b> .735"	1161U	Opt for 1194, 1194H, 5194, 5194H	Corbin Russwin interchangeable core (A01)
.572"	1160L	Opt for 1194, 1194H, 5194, 5194H	Adams Rite MS 1800 series locks and 4700 series latches.	.715"	1161T	Opt for 1123, 1152, 1186, S1052H, 5152, U5152	Corbin Russwin fixed core (A01)
.715"	1161	Std for 1123, 1152, S1052H, 5152, U5152	Obsolete cast iron mortise locks.		10-6120- 9010	Cam Disc	Filler for hollow mill cams.

All cams and cam disc illustrated actual size.