


ZERO CAM LIFT MORTISE HINGES


Mortise-Type Cam Hinges for use with EMI/RFI and sound-insulating doors utilizing acoustical seals. The cam action greatly improves the sealing characteristics along the door perimeter, lifting and lowering the door with the swing. The CAM LIFT Hinges are available for right or left-hand swinging doors. CAM LIFT Hinges will not bind door closures when doors are hung within accepted industry standards (Tested with LCN 4041 Series original).
Finish: 630 (US32D). Sold in pairs.




#Z950 L.H. Shown
#Z9500 (not shown)



#Z953
L.H. Shown



#Z955
L.H. Shown



Part #	Door Rating (1 1/2 pairs)	Screw Size (metal doors)	Lift (180° opening)
Z955	Up to 200 lbs.	12-24 x 3/4" UC	3/16"
Z953	Up to 300 lbs.	12-24 x 3/4"	1/4"
Z950	Up to 500 lbs.	12-24 x 3/4"	5/16"
Z9500	Up to 900 lbs.	5/16-18 x 3/4"	5/16"



#7250Z
12-24 x 3/4"



#7255Z
12-24 x 3/4" UC



#7252ST
5/16-18 x 3/4"



#7251Z
12 x 1 1/4" SMS
For wood doors

Z CAM LIFT HINGES SPECIFICATIONS


- HINGE:** 1020 Stainless Steel, precision investment cast.
- PIN:** Hardened tool steel. Hardened & chrome finished to Rockwell C 60 to meet ASME/ANSI B 18.3 specs.
- TYPE:** Mortise/ Handed - specify right or left hand.
- SPECS:** Minimum clearance at head of frame is 3/16". For doors greater than 1-3/4" clearance is 1/4".
- FINISH:** 630 (US32D)
- NOTE:** For Z950 and Z9500 screws must be engaged no less than .350" in ASTM A-36 steel reinforcement.

Full Mortise Hinge

Stainless Steel and Steel hinges. Five knuckle, two ball bearings, NRP pin. A non-ball bearing hinge is also available.



#Z961



Part #	Finish	Material	Size	Thickness
ZBB 960	630 (32D)	Stainless Steel	4.5" (114.3) x 4.5" (114.3)	.134" (3.4) Gauge
ZBB 961	626 (26D)	Steel Dull Chrome	4.5" (114.3) x 4.5" (114.3)	.134" (3.4) Gauge
ZBB 991	626 (26D)	Steel Dull Chrome	5.0" (127) x 4.5" (114.3)	.134" (3.4) Gauge
Z 961	600 (USP)	Steel Primed	4.5" (114.3) x 4.5" (114.3)	.134" (3.4) Gauge

Packed AWS & AMS - Boxed pair & half