

## PD400 series padlocks



### features

**Case:** Chrome Plated Steel

**Shackle:** High strength molybdenum alloy steel. Rust resistant with a chrome finish. Optional brass shackles available.

**Shackle Diameter:** 5/16" (8mm)

**Shackle Locking:** Two hardened steel balls at heel and toe of shackle.

**Extended Shackles:** Optional shackles with 2" and 3" vertical clearance are available to order.

**Chains:** Optional 9" chains available with clevis around shackle. To order with padlocks specify suffix:


- "S42A" = brass chain
- "S42S" = steel chain

See page 15 for chains ordered separately.

**Keying:** 6-pin only. Furnished standard with Yale 1801 type component cylinder; available KA, KD or master keyed only (not available 0-bitted or unassembled). Not re-keyable.

**Keys:** Two nickel silver change keys supplied with each padlock.

### dimensions and details



Model Numbers		Description	Vertical Clearance (R)	Overall Height (H)	Pins
Molybdenum Steel Shackle	Brass Shackle				
PD416	PD416B	Fixed Core	1-1/16" (27mm)	3-3/4" (95mm)	6
PD2416	PD2416B	Fixed Core	2" (51mm)	4-3/8" (111mm)	6
PD3416	PD3416B	Fixed Core	3" (76mm)	5-3/8" (137mm)	6

Note: All dimensions are in inches and are to the nearest 1/16" (2mm). Dimensions are nominal.

## PD500 series padlocks



Available in fixed core, large format interchangeable core (LFIC), and small format interchangeable core (SFIC).

### features

**Case:** Solid Brass

**Shackle:** High strength molybdenum alloy steel. Rust resistant with a chrome finish. Optional brass shackles available.

**Shackle Diameter:** 3/8" (10mm) or 5/16" (8mm)

**Shackle Locking:** Two hardened steel balls at heel and toe of shackle.

**Extended Shackles:** Optional shackles with 2" and 3" vertical clearance are available to order.


**Chains:** Optional 9" chains available with clevis around shackle or riveted to case. To order with padlocks specify suffix:

- for clevis around shackle
  - "S42A" = brass chain
  - "S42S" = steel chain
- for clevis riveted to case
  - "C42A" = brass chain
  - "C42S" = steel chain

See page 15 for chains ordered separately.

**Keys:** Two nickel silver change keys supplied with each padlock. Control key quantity must be specified for interchangeable core.

### Dimensions and Details:



Model Numbers		Description	Case Height (C)	Vertical Clearance (R)	Diameter (S)	Overall Height (H)	Pins	
Molybdenum Steel Shackle	Brass Shackle							
PD514	PD514B	LFIC	2-5/16" (59mm)	1-1/16" (27mm)	5/16" (8mm)	3-3/4" (95mm)	6	
PD2514	PD2514B	LFIC		2" (51mm)		4-3/8" (111mm)	6	
PD3514	PD3514B	LFIC		3" (76mm)		5-3/8" (137mm)	6	
PD515	PD515B	SFIC	2-1/4" (57mm)	1-1/16" (27mm)		3-5/8" (91mm)	6 or 7	
PD2515	PD2515B	SFIC		2" (51mm)		4-9/16" (115mm)	6 or 7	
PD3515	PD3515B	SFIC		3" (76mm)		5-5/8" (142mm)	6 or 7	
PD516	PD516B	Fixed Core	2-5/16" (59mm)	1-1/16" (27mm)		3/8" (10mm)	3-3/4" (95mm)	6
PD2516	PD2516B	Fixed Core		2" (51mm)			4-3/8" (111mm)	6
PD3516	PD3516B	Fixed Core		3" (76mm)			5-3/8" (137mm)	6
PD524	PD524B	LFIC		1-1/16" (27mm)			3-3/4" (95mm)	6
PD2524	PD2524B	LFIC		2" (51mm)			4-3/8" (111mm)	6
PD3524	PD3524B	LFIC		3" (76mm)			5-3/8" (137mm)	6
PD534	PD534B	LFIC		1-1/16" (27mm)	3-3/4" (95mm)	7		
PD2534	PD2534B	LFIC		2" (51mm)	4-3/8" (111mm)	7		
PD3534	PD3534B	LFIC		3" (76mm)	5-3/8" (137mm)	7		
PD525	PD525B	SFIC		2-5/16" (59mm)	1-1/16" (27mm)	3/8" (10mm)	3-3/4" (95mm)	6 or 7
PD2525	PD2525B	SFIC			2" (51mm)		4-3/8" (111mm)	6 or 7
PD3525	PD3525B	SFIC			3" (76mm)		5-3/8" (137mm)	6 or 7
PD526	PD526B	Fixed Core	1-1/16" (27mm)		3-3/4" (95mm)		6	
PD2526	PD2526B	Fixed Core	2" (51mm)		4-3/8" (111mm)		6	
PD3526	PD3526B	Fixed Core	3" (76mm)		5-3/8" (137mm)		6	

Note: All dimensions are in inches and are to the nearest 1/16" (2mm). Dimensions are nominal.