



FIGURE 7074 CAP			
Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	1¼	0.3
25	33.4	32	0.1
1¼	1.660	1¼	0.4
32	42.2	32	0.2
1½	1.900	1¼	0.5
40	48.3	32	0.2
2	2.375	1	0.5
50	60.3	25	0.2
2½	2.875	1	0.7
65	73.0	25	0.3
3 O.D.	2.996	1	0.8
76.1	76.1	25	0.4
3	3.500	1	1.1
80	88.9	25	0.5
4	4.500	1⅛	2.8
100	114.3	29	1.3
5½ O.D.	5.500	1⅞	4.0
139.7	139.7	29	1.8
5	5.563	1⅞	4.0
125	141.3	29	1.8
6½ O.D.	6.500	1⅞	6.0
165.1	165.1	29	2.7
6	6.625	1¾	6.0
150	168.3	33	2.7
8	8.625	1½	12.5
200	219.1	38	5.7
10	10.750	1½	21.9
250	273.1	38	9.9
12	12.750	1½	33.8
300	323.9	38	15.3

Additional sizes available, see Gruvlok Catalog or contact an Anvil Representative.

For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

- Available galvanized.
 * When ordering, refer to product as FP7074.

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile Iron conforming to ASTM A-536

COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			