

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 26
Roof & Flashing Sealant



MATERIAL SAFETY INFORMATION SERVICE

Hercules Chemical Company Inc.
 111 South Street
 Passaic NJ 07055
 Phone (800) 221-9330
 Fax (800) 333-3456

Date Prepared: 12/19/1989 Last Reviewed: 5/2/2001

Meets OSHA 29 CFR 1910.1200

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s), CAS Numbers)	OSHA PEL	ACGIH TLV	Other Limits	Upper Bound Limit if SARA Reportable
*These components are totally encapsulated in paste.				
Asphalt (8052-42-4)	400PPM	500PPM	N/A	--
Mineral Spirits (64741-41-9)	400PPM	500PPM	N/A	--
Attapulgite Clay (8031-18-3)*	N/A		N/A	--
Active Cationic Salts (2871-67-9)*	N/A	N/A	N/A	--
Cellulosic Fibers (9004-34-6)*	N//A	N/A	N/A	--

HMIS Hazard Rating: Health: 2 Flammability: 2 Reactivity: 0 Personal Protection: C

Section 3 - Physical/Chemical Characteristics

Boiling Point (°C):	Specific Gravity (H2O = 1):	Vapor Density (Air = 1):	Vapor Pressure (mm Hg):
315	1.1	3.9	@20° C 1
Melting Point (° F)	Evaporation Rate: (Butyl Acetate = 1)	Solubility in Water:	
N/A	0.1	Negligible	
Appearance And Color:	Black paste	Odor:	Mild solvent odor

Section 4 - Fire And Explosion Hazard Data

Flash Point:	Flammable Limits:	LEL:	UEL:
100° F TCC		1.0%	7.0%

Extinguishing Media: Foam, Carbon Dioxide, Water Fog

Special Firefighting Procedures:
 Do not use water as liquid

Unusual Fire And Explosion Hazards:
 None

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable **Conditions To Avoid:** None
Incompatibility (Materials To Avoid): None known
Hazardous Decomposition: Carbon monoxide and carbon dioxide

Hazardous Polymerization: None known

Section 6 - Health Hazard Data

Routes of Entry: **Inhalation** YES/Primary **Skin** YES/Primary **Ingestion** YES/Secondary

Health Hazards:

Inhalation of high vapor concentrations can cause dizziness and headaches. Prolonged skin contact can lead to dry and irritated skin possibly causing dermatitis.

Carcinogenicity: **NTP** NO **IARC** NO **OSHA Regulated** NO

Signs And Symptoms of Exposure:

Dizziness, nausea

Medical Conditions Generally Aggravated By Exposure:

N/A

Emergency And First Aid Procedures:

Remove to fresh air and call physician as soon as possible. If unconscious, give artificial respiration. If splashed in eyes, flush thoroughly with water.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:**Steps To Be Taken In Case Material Is Released Or Spilled:**

Remove all sources of ignition (Flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Remove with inert absorbent and non-sparking tools.

Waste Disposal Method:

Dispose in accordance with local, state and federal regulations. Incinerate in approved facility. Do not incinerate in closed containers.

Precautions To Be Taken In Handling And Storing:

Do not store above 120° F. Store large quantities in buildings designed and protected for storage of NFPA combustible liquids.

Other Precautions:

None

Section 8 - Control Measures:**Respiratory Protection:**

In confined spaces or other circumstances where adequate ventilation cannot be assured use NIOSH-approved respirator, positive pressure airline mask, or self contained breathing apparatus.

Ventilation: Local Exhaust Adequate Special N/A
Mechanical N/A

Gloves: Regular working gloves. Other: N/A

Eye Protection: Use safety eyewear.

Other Protective Clothing: Clothing that prevents skin contact with material.

Work/Hygienic Practices Prevent prolonged skin contact with contaminated clothing.



FACTS
axed
AST!

For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.