

Product Information

ADA compliant	
Applicable lavatories:	
15" (38.1 cm) x 12" (30.5 cm), with overflow, with clamps	K-2209
17" (43.2 cm) x 14" (35.6 cm), with overflow, with clamps	K-2210
17" (43.2 cm) x 14" (35.6 cm), with glazed underside, without overflow, with clamps	K-2210-G
17" (43.2 cm) x 14" (35.6 cm), with overflow, without clamps	K-2210-L
17" (43.2 cm) x 14" (35.6 cm), without overflow	K-2210-N
19" (48.3 cm) x 15" (38.1 cm), with overflow, with clamps	K-2211
19" (48.3 cm) x 15" (38.1 cm), with glazed underside, without overflow, with clamps	K-2211-G
19" (48.3 cm) x 15" (38.1 cm), with overflow, without clamps	K-2211-L

Fixture*:	Basin area	Water depth
K-2209	15" (38.1 cm) x 12" (30.5 cm)	4" (10.2 cm)
K-2210/K-2210-L/ K-2210-N/K-2210-G	17" (43.2 cm) x 14" (35.6 cm)	4" (10.2 cm)
K-2211/K-2211-G/ K-2211-L	19" (48.3 cm) x 15" (38.1 cm)	4" (10.2 cm)
Drain hole	1-3/4" (4.4 cm) D.	
* Approximate measurements for comparison only.		

Included components:	
Basin clamp assembly (not included with K-2210-L and K-2211-L)	52047
Cut-out template, K-2209	85838-7
Cut-out template, K-2210	1002975-7
Cut-out template, K-2211	1018997-7

Installation Notes

Install this product according to the installation guide.

Supplied basin clamp assemblies require 1" (2.5 cm) minimum countertop thickness. Installer must supply anchors for thinner countertops.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

K-2209: (X) = 14" (35.6 cm), (Y) = 17" (43.2 cm)
 K-2210: (X) = 16-1/4" (41.3 cm), (Y) = 19-1/4" (48.9 cm)
 K-2211: (X) = 17-1/4" (43.8 cm), (Y) = 21-1/4" (54 cm)

