


## Accessories and Tools

### Application

Package of 100 dial stop pins to insert in dial ends to limit the high or low setting of room thermostats.

**AT-104**

### Dial Stop Pins



### Specifications


- Electric.
  - All except TA-121, TC-114.
- Electronic.
  - TP-810x.
  - TP-8232.
  - TS-5191.
  - TS-5711.
  - TS-811x.
- Pneumatic.
  - All TK-1xxx and TK-5xxx except TK-17xx, TK-18XX.

### Application

Immersion well for use with 3/8 in. (10 mm) temperature bulbs.

**AT-201, AT-203, AT-206**

### Immersion Well



### Specifications

- Ambient temperature limits: -40 to 350°F (-40 to 177°C).
- Refer to F-18895 for complete applications.

Model No.	Material	Dimensions						Application Limitations at 250°F (121°C) Fluid Temp.		Used With
		O.D. in. (mm)	Insertion Probe O.D. Max.	Insertion Length in. (mm)	Overall Well Length in. (mm)	Internal Fitting Thread	External Fitting in.	Max. Recom. Velocity FPS (m/s)	Max. Recom. Static Pressure psig (kPa)	
AT-201 <sup>a</sup>	Copper	1/2 (13) <sup>b</sup>	.3750	9-1/2 (241)	10-1/4 (260)	5/8-18	3/4 MNPT	11 (3.3)	250 (1728)	TC-28x, TC-4x1x, TC-4x2x, TC-4x5x, TK-6024, TK-6124, TKS-8000's
AT-203 <sup>a</sup>	Stainless Steel	1/2 (13) <sup>b</sup>	.395	9-1/2 (241)	10-1/2 (267)		3/4 MNPT	20 (6.1)	500 (3448)	Same as AT-201
AT-206	Copper	1/2 (13) <sup>b</sup>	.420	4-1/2 (114)	5-13/16 (148)	—	1/2 MNPT	11 (3.3)	250 (1728)	TC-4x1x, TC-4x2x, TC-4x5x, TK-6024, TK-6124

<sup>a</sup> Requires AT-209 for TC-4x1x, TC-4x2x, TC-4x5x, TK-6024, TK-6124.

<sup>b</sup> For 3/8 in. (10 mm) diameter bulbs.