



PRODUCT SPECIFICATIONS: PipeBurst Pro

1" Stainless Steel TickerValve:

- Waterproof Motor Enclosure – NEMA 6P, IPX-8, and NEMA 7D Rated - USCG Approved
- Waterproof - Ignition Proof Enclosure
- Enclosure Material: Nylon
- NSF 61 Certification
- UPC Certification
- Lead Free Certification
- Powered via VIP Panel
- Easy access Deutsch plug assembly
- Max Amps: 5
- Voltage: 12vdc Nominal
- Valve SloFlow "Open" Time: 3 Seconds
- Valve Quick "Close" Time: $\frac{3}{4}$ Second
- Valve Size: 1" NPT(F), Full Port Flow
- Valve Pressure Rating: 600 psi
- Valve Material/Design: 316 Stainless Steel/3 Piece
- Valve Seats/Seals: PTFE/Fluorocarbon Elastomer
- Manual Over-Ride Lever
- Overall Dimensions: 8.5" H x 5" W x 4" D
- Weight: 4 lb. Nominal

VIP (Valve Interface Panel):

- UL Rated Power Supply – 12 or 24 volts
- Voltage: 12vdc Nominal
- Watts: Charger Idling: 2.7
- Charging Battery: 9 Watts
- Motor Running: 28 Watts
- Powered via 18vdc/120v AC Wall Adapter and Internal Backup SLAB (*Sealed Lead Acid Battery*)
- Dimensions: 6.8" W x 6.25" H x 5" D
- Enclosure Material: ABS
- Wall Mountable Tabs Spaced at 4" Wide Center to Center
- Internal "Chirper" Alarm
- Internal "Freeze" Sensor/Alarm
- Wireless Device Control Capacity: Up to 256
- Transmit/Receive Frequency: 433.92 MHz
- Wireless Range: 300 Feet (*Dependent on Local Structural Conditions*)

- LED Status Display
- Buttons for System Control

FloodBug Water Sensor:

- UL Rated Power Supply – 12 or 24 volts
- Voltage: 3vdc Nominal
- Powered via AC Wall Adapter or 2-AA Alkaline Batteries
- Battery Life: Approximately 12 Months
- Dimensions: 4.4" L x 2.5" W x 1.5" H
- Internal "Chirper" Alarm
- Water Sensors: Gold Plated
- Enclosure Material: ABS
- Transmit/Receive Frequency: 433.92 MHz
- Wireless Range: 300 Feet (*Dependent on Local Structural Conditions*)

SideKick (FloodBug Extender Sensor):

- Wire Length: 5' ultra-flexible "mini" wire when connected to FloodBug
- Dimensions, Nominal: 2" Diameter x 3/8" H
- Material: 316 Stainless Steel Housing
- Water Sensors: Gold Plated
- SideKick plugs directly into VIP with 20' ultra-flexible "mini" wire

FloTrax (Wireless Control Panel):

- UL Rated Power Supply – 12 or 24 volts
- Voltage: 3vdc Nominal
- Powered via AC Wall Adapter or 2-AA Alkaline Batteries
- Battery Life: Approximately 6 Months as a battery backup (*Dependent on Use*)
- Dimensions: 6" W x 5.2" H x 1.7" D
- Internal "Chirper" Alarm
- Internal "Freeze" Sensor
- Programmable User Settings via LCD Display
- Enclosure Material: ABS
- Transmit/Receive Frequency: 433.92 MHz
- Wireless Range: 328 Feet (*Dependent on Local Structural Conditions*)