



PeerlessBoilers.com

Series MI™

- Packaged Residential • Natural Draft Venting
- Atmospheric Gas - Spark Ignition
- Hot Water Boilers • Natural or LP Gas

GAS-FIRED



Standard Equipment:

- Cast Iron Sections - Factory Tested and Assembled with Steel Push Nipples
- Deluxe Powder Coated Steel Jacket
- 30 PSI Safety Relief Valve
- Spark Ignition
- Boiler Reset Control with Circulator Relay and LWCO
- Drain Valve
- Temperature-Pressure Gage

- Electrically Operated Auto. Vent Damper
- Flame Rollout Safety Shutoff Switch
- Vent Safety Shutoff Switch
- Taco Circulator

Optional Equipment:

- Grundfos Circulator
- 50 PSI Safety Relief Valve
- Non-Combustible Floor Pan

SERIES MI™ BOILER RATINGS

Series MI™					AFUE ³ , %	Water Content, Gallon
Boiler Model	Input, MBH	Heating Capacity ³ , MBH	Net Ratings Water ^{1,2} , MBH	APRI CERTIFIED [®] www.apriboiler.org		
MI-03	70	58	50	82.2	4.72	
MI-04	105	86	75	82.1	6.00	
MI-05	140	115	100	82.0	7.28	
MI-06	175	143	124	82.0	8.56	
MI-07	195	160	139	82.0	9.84	
MI-08	227.5	186	162	82.0	11.12	
MI-09	260	211	183	82.0	12.40	

1 Net water ratings based on an allowance of 1.15.

2 Consult factory before selecting a boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.

3 Heating Capacity and Annual Fuel Utilization Efficiency (AFUE) ratings are based on U.S. Government test.

NOTE: Minimum Supply Gas Pressure: Standard 5 in. W.C. Natural Gas - 11 in. W.C. LP Gas.

Ordering Information:

Example:

MI - 03 - SPRK - WPC - N

Series

Sects.

Spark Ignition

WPC=Water Package
w/Circulator

Natural Gas (Substitute "LP" for LP)

OPTIONAL EQUIPMENT TRADE PRICES

Description	Trade Price	
50 PSI Safety Relief Valve	N/C	
Circulator:		
Taco 0010 (03-08) I.L.O. Std.	\$135	
Gdfs UP 26-64 (03-09) I.L.O. Std.	\$198	
Gdfs UP 15-42F (03-08)	N/C	
Non-Combustible Floor Pan:		
Code No.		
Model 03	90700	\$235
Model 04	90701	\$245
Model 05	90702	\$268
Model 06	90703	\$276
Model 07	90704	\$276
Model 08	90705	\$304
Model 09	90706	\$319

Optional circulator and relief valve must be indicated on order.

Five and ten-year Extended Warranties available; see page 120 for details.

For Additional MI™ Product Information:

See Product Catalog Literature for Complete Product Specifications.

Series MI™

HYDROLEVEL (3200) SPARK IGNITION w/DAMPER TRADE PRICES (WPC')

Code No. N	Code No. LP	Series	No. of Sections	Intermittent Ignition w/Damper	Approx. Shipping Weight (lbs)	Trade Price
0103033	0103035	MI	03	SPRK	282	\$2,363
0104006	0104004	MI	04	SPRK	353	\$2,579
0105001	0105003	MI	05	SPRK	428	\$2,936
0106004	0106006	MI	06	SPRK	479	\$3,437
0107004	0107006	MI	07	SPRK	568	\$3,761
0108004	0108006	MI	08	SPRK	601	\$4,224
0109001	0109003	MI	09	SPRK	681	\$4,581

CRATE DIMENSIONS (WPC')

Boiler Model	Width	Depth	Height
MI-03	28-1/2"	30-7/8"	36-1/2"
MI-04	28-1/2"	30-7/8"	36-1/2"
MI-05	35-1/2"	30-7/8"	36-1/2"
MI-06	35-1/2"	30-7/8"	36-1/2"
MI-07	42-1/4"	33-7/8"	36-1/2"
MI-08	42-1/4"	33-7/8"	36-1/2"
MI-09	45-1/2"	33-7/8"	36-1/2"

(1) Water Package with Circulator

