


FIG. 110CT COPPER PLATED CLEVIS HANGER, TUBING SIZE

FIG. 110CTI EPOXY COATED (*COPPER-GARD*) CLEVIS HANGER, TUBING SIZE



"E" dimension includes exposed rod threads beyond bottom of the hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



Material: Carbon Steel.

Finish: Copper plated (110CT) or Copper epoxy coated (*COPPER-GARD*). *COPPER-GARD* products offer superior corrosion protection due to the epoxy coating over electro-galvanized steel. The alternative copper plating, that has been done historically, identifies the product and is not intended for protection. Refer to MSS SP-58, 13.3.

Service: Designed for the suspension of stationary copper tubing.

Approvals: Complies with Federal Specifications WW-H-171-E (Type# 1), A-A-1192 A (Type# 1), and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 1).

Ordering: Specify tube size and figure number.

TUBE SIZE	PIPE OD	MATERIAL SIZE		BOLT	A	B	C	E	F	WGT EACH (lbs)	MAX REC LOAD(lbs)
		TOP	BOTTOM								
1/2	0.625	18ga x 7/8	18ga x 7/8	1/4	3/8	1 7/8	2 3/16	1 1/8	1/2	0.12	150
3/4	0.875	18ga x 7/8	18ga x 7/8	1/4	3/8	1 3/4	2 1/8	1	1/2	0.12	250
1	1.125	18ga x 7/8	18ga x 7/8	1/4	3/8	1 13/16	2 5/16	1 1/16	1/2	0.12	250
1 1/4	1.375	18ga x 7/8	18ga x 7/8	1/4	3/8	2 1/8	2 3/4	1 5/16	3/4	0.12	250
1 1/2	1.625	18ga x 7/8	18ga x 7/8	1/4	3/8	2 1/2	3 1/4	1 3/4	15/16	0.18	250
2	2.125	14ga x 7/8	16ga x 7/8	1/4	3/8	2 15/16	4	2 3/16	1 1/16	0.24	250
2 1/2	2.625	12ga x 1 3/16	14ga x 1 3/16	1/4	1/2	4 7/8	5 3/4	3 3/8	2 1/16	0.58	350
3	3.125	12ga x 1 3/16	14ga x 1 3/16	1/4	1/2	4 1/2	6 1/8	3 7/16	2	0.60	350
3 1/2	3.625	12ga x 1 3/16	14ga x 1 3/16	5/16	1/2	4 3/4	6 1/2	3 11/16	1 13/16	0.66	350
4	4.125	11ga x 1 3/16	14ga x 1 3/16	5/16	1/2	5 7/8	7 7/8	4 3/4	2 9/16	1.02	400
5	5.125	8ga x 1 1/4	8ga x 1 1/4	3/8	5/8	5 7/8	8 3/4	4 3/4	1 5/8	1.68	550
6	6.125	8ga x 1 1/4	8ga x 1 1/4	3/8	5/8	6 1/16	9	4 3/4	1 1/2	1.84	550