

Permanent Split Capacitor Direct Drive Fan Single Shaft 5.0" Diameter Open, Air Over




APPLICATIONS:

To meet manufacturer's requirements for direct drive fan and blowers.

FEATURES:

- Reversible Unless Noted
- Sleeve Bearings have All Angle Thrust System
- Suitable for Use With 370V Capacitors
- Continuous Duty, Air Over
- 24" Line Leads unless otherwise noted
- Automatic Reset Thermal Overload Protector
- Connection & Capacitor Information Furnished in Nameplate Data
- **Discount Symbol: DS-3HAC**



Permanent Split Capacitor, 5.0" Diameter, Stud or Hub Ring Mount (2.5")

HP	RPM/ Spds.	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt. (lbs)	Notes
1/6	1075	115	6479	\$162	Sleeve	4.0	2.8	4.1	--	3.8	7.9	--	9	H11
1/5	1075/3	208-230	8952	\$206	Sleeve	5.0	1.6	4.0	5.3	4.9	9.9	--	11	
	1075/4	115	1268	\$150	Sleeve	4.0	3.4	3.5	4.6	4.1	8.7	1	10	98
1/4	1075	115	6480	\$112	Sleeve	7.5	4	5.0	--	4.1	9.1	--	9	H11
	1050/3	115	1390	\$160	Sleeve	7.5	2.8	4.0	4.9	4.3	8.9	1	13	H24
	1050/3	208-230	1391	\$163	Sleeve	7.5	1.5	4.0	4.9	4.3	8.9	1	13	H24
1/3	1075/3	115	8955	\$136	Sleeve	15.0	3.8	4.0	5.1	--	10.2	0.75	13	

Note 98 Class B Insulation
 Note H11 Band Mounting
 Note H24 Hub Rings Not Included

† All marks shown within this document are properties of their respective owners.

