



End cap


- For copper manifolds
- Type L copper
- Female copper tube size, female pipe thread

Note

½" FPT for draw-off (purge valve) and ⅝" FPT for automatic air vent (bottle vent).

Model 2834.5US

C	FPT1	FPT2	Wt [lb]	Quantity	Part No	DG
1	½	⅝	0.400	1	17144	4
1½	½	⅝	0.610	1	17125	4
2	½	⅝	0.965	1	17106	4



Bracket

- For copper manifolds
- Galvanized steel

Model 2878.927

d	Wt [lb]	Quantity	Part No	DG
1	0.348	2	17145	4
1½	0.002	1	17126	4
2	0.002	1	17107	4



Manifold cabinet

- Galvanized steel, epoxy powder-coated finish

Model 2879.6US

W [in]	H [in]	D [in]	Wt [lb]	Quantity	Part No	DG
21	30	4½	28.975	1	15800	4
27	30	4½	33.990	1	15801	4
45	30	4½	49.986	1	15802	4



Lock assembly

- Suitable for manifold cabinet

Model 2879.6US

Components

(2) keys

Note

Part No 15802 requires two locks.

Model 2857.7US

Wt [lb]	Quantity	Part No	DG
0.145	1	15217	4

Control



Basic heating control

- For controlling system water temperature based on outdoor reset
- Modulating mixing valve control, boiler activation

Components

Supply sensor, outdoor sensor

Model 2871.0US

Wt [lb]	Quantity	Part No	DG
3.464	1	16015	4



Indoor sensor

- Use with basic heating control

Model 2871.0US

Model 2871.2US

Wt [lb]	Quantity	Part No	DG
0.150	1	16016	4



Multiple outdoor sensor

- For up to (4) basic heating controls to share a single outdoor sensor
- Use with basic heating control

Model 2871.0US

Components

10kΩ thermistor

Model 2871.3US

Wt [lb]	Quantity	Part No	DG
0.200	1	16020	4