


FIG. 21 STEEL C-CLAMP

FIG. 21L STEEL C-CLAMP WITH LOCKNUT, DOMESTIC

FIG 21LI STEEL C-CLAMP WITH LOCKNUT



- Material:** Carbon steel, 304 stainless steel (21LSS) and 316 stainless steel (21LSX).
- Finish:** Plain, electro-galvanized.
- Service:** Designed for attaching hanger rod to the bottom flange of a beam. Features the ribbed design for added strength. Hardened steel cup point set screw secures clamp to beam.
- Approvals:** UL - U.L.C. listed $\frac{3}{8}$ and $\frac{1}{2}$ ($\frac{1}{2}$ for 4" IPS max) **with locknut only.**
FM approved for $\frac{3}{8}$ only **with and without locknut.**
Complies with Federal Specification WW-H-171-E (Type# 23), A-A-1192 A (Type# 23), Manufacturers' Standard Society SP-58 and MSS SP-69 (Type# 23)
- Ordering:** Specify rod size, figure number and finish.
- Notes:** See MSS SP-69 for proper set screw torque recommendations.



SIZE A	SET SCREW	C	D	E	F	MAX PIPE SIZE	WGT EACH (lbs)		MAX REC LOAD (lbs)
							21 (W/OUT NUT)	21L (W/NUT)	
$\frac{3}{8}$ -16	$\frac{3}{8}$ -16	2 $\frac{3}{8}$	2 $\frac{3}{8}$	1	$\frac{3}{4}$	4	.38	.40	400
$\frac{1}{2}$ -13	$\frac{3}{8}$ -16	2 $\frac{3}{8}$	2 $\frac{3}{8}$	1	$\frac{3}{4}$	4	.38	.40	500
$\frac{5}{8}$ -11	$\frac{1}{2}$ -13	2 $\frac{3}{8}$	2 $\frac{5}{16}$	$\frac{7}{8}$	$\frac{3}{4}$	5	.56	.60	550
$\frac{3}{4}$ -10	$\frac{5}{8}$ -11	2 $\frac{3}{8}$	2 $\frac{5}{16}$	$\frac{7}{8}$	$\frac{3}{4}$	6	.60	.68	630
$\frac{7}{8}$ -9	$\frac{3}{4}$ -10	3	3 $\frac{5}{16}$	1 $\frac{1}{4}$	1	8	1.76	1.88	1200