

Refrigeration Condenser Fan 5.0" and 5.6" Diameter Open Dripproof, Totally Enclosed, Air Over and Open Air Over

APPLICATIONS:

Condenser cooling fan motors to meet manufacturer's requirements for commercial refrigeration units.

FEATURES:

- OEM Direct Replacements
- Single Speed
- Automatic Reset Thermal Overload Protector
- Suitable for use with 370V Capacitors
- **Discount Symbol: DS- 3HAC**




Figure A




Figure B

5.0" Diameter, 3/8" Diameter Shaft

HP	RPM	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Mount	Ship Wt. (lbs)	Notes	OEM
1/20	1300	230	1775P	\$148	SAB	-	0.5	2.0	3.8	6.9	Hub Ring	7	98	TE
1/15	1300	230	1779P	\$154	SAB	-	0.62	2.0	3.8	6.9	Hub Ring	8	98	TE

5.6" Permanent Split Capacitor

HP	RPM	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Mount	Ship Wt. (lbs)	Notes	OEM
1/6	1550	208-230	6128	\$263	SAB	3.0	1.1	2.3	3.6	7.2	Resilient	17	64,H36	CO
	1550	208-230	1645	\$263	Ball	3.0	1.4	2.1	3.8	6.4	Stud	12	H35	HU
1/5	1075	208-230	1648	\$244	Ball	4.0	2.0	2.5	4.3	7.8	Stud	13	H35	HU
1/4	1550	230	6124	\$242	SAB	5.0	2.1	3.0	4.1	7.1	Band	13	64,H36	CO
	1625	208-230	6129	\$273	SAB	5.0	1.5	2.3	4.3	7.6	Resilient	17	64,H36	CO
	1625	230	3042	\$239	Ball	4.0	1.4	1.5	5.1	7.7	Hub Ring	12	64,H4,H36	TY
	1350	230	8330	\$241	SAB	4.0	1.9	2.2	4.3	7.7	3 Lugs	12	64,98,H36,H42	TE
	1625	380/420/460	8331	\$257	SAB	4.0	0.95	2.2	4.3	7.7	3 Lugs	12	64,98,H36,H42	TE
1/3	1625	208-230	6127	\$264	SAB	4.0	2.2	1.75	5.8	8.7	Resilient	17	64,H45	CO
	1625	208-230	7232	\$173	SAB	6.0	2.9	3.7	4.6	9.6	Hub Ring	16	64,H35	HR
1/2	1725	208/230	644	\$250	Ball	5.0	2.7	3.5	5.1	8.6	Stud	15	H18,H36	HU

CO = Copeland^{®†}

HU = Hussmann^{®†}

HR = Hill Refrigeration^{®†}

TE = Tecumseh^{®†}

TY = Tyler^{®†}

Note 64 Capacitor Included
 Note 98 50/60 Hertz
 Note H4 2-1/4" Hub Rings
 Note H18 Conduit Box

Note H35 Open Air Over
 Note H36 Open Dripproof
 Note H42 Shaft Down
 Note H45 Totally Enclosed Air Over

† All marks shown within this document are properties of their respective owners.

