



# Gruvlok® SPF/Anvil™ Lubricants

- Gruvlok® SPF/Anvil™ Xtreme Lubricant™
- Gruvlok® SPF/Anvil™ Quick Dry Lubricant™
- Gruvlok® SPF/Anvil™ Standard Lubricant™

## Gruvlok SPF/Anvil Xtreme Lubricant

Gruvlok SPF/Anvil Xtreme Lubricant has been developed for use with Gruvlok and SPF couplings in services where improved lubrication is beneficial. This Xtreme lubricant has an operating temperature range from -65°F to 400°F, well exceeding the temperature range of Gruvlok and SPF gaskets. This lubricant is waterproof, thereby eliminating water wash-out and it will not dry out in the absence of water. There are five primary applications where the Xtreme Lubricant will provide increased benefits: low temperature applications (below -20°F), high temperature applications (above 180°F), applications where increased pipe joint flexibility is needed, lubrication of gaskets in copper systems, and for the lubrication of gaskets on HDPE couplings. Since it is formulated from a non-hydro carbon base, it can be used with EPDM, Nitrile and Fluoroelastomer gasket materials. **It is not to be used with silicone gaskets.**

- In low temperature applications the gasket will shrink, thereby lowering the sealing force on the gasket sealing lips. The temperature change will also force the gasket to slightly re-position itself. This will cause pipe end sealing surfaces, with small cuts or damage, to become more susceptible to leakage. Gruvlok SPF/Anvil Xtreme Lubricant will maintain it's lubricating properties at lower temperatures allowing a properly lubricated pipe end and gasket (assembly) to re-position itself during temperature cycles.
- For high temperature service and copper systems, it is required that the gasket be lubricated not only on the outside, as with the normal installation of a Gruvlok or SPF gasket, but also on the inside. Lubrication on the inside of the gasket is easily accomplished by turning the gasket inside out and applying the lubricant. Xtreme Lubricant will maintain it's lubricating properties at higher

temperatures, allowing a properly lubricated pipe end and gasket assembly to re-position itself during temperature cycles. Lubrication of the pipe end and gasket will help the gasket to adjust into the proper sealing position during temperature cycles. The lubricant on the interior of the gasket will act to improve the chemical resistance of the gasket material by providing a thin lubricant barrier between the piping system fluid and the gasket surface. This is particularly important at higher temperatures where oxidizing agents in the piping system become more aggressive. **However, gasket chemical compatibility must still be considered.**

- The Gruvlok SPF/Anvil Xtreme Lubricant has been formulated from low viscosity, non-petroleum based oils to ease spreading of the lubricant. In applications where pipe movement is expected, proper lubrication of the gasket's exterior assists the gasket into the proper sealing position as pipe system movement occurs. This lubricating film enhances our flexible coupling gasket's ability to compensate for axial, transverse and rotational pipe movements.
- Gruvlok SPF/Anvil Xtreme Lubricant is the only lubricant that is to be used with Gruvlok and SPF couplings/gaskets in HDPE and copper piping systems. It's low temperature capability and lubricity ensure a highly reliable connection.

Gruvlok SPF/Anvil Xtreme Lubricant is a Teflon fortified white, tasteless and odorless grease made from Silicone Oil and other ingredients that are safe to ingest. It is sanctioned by the FDA under C.F.R. 21.172.878 & 21.177.1550 (Incidental Food Contact).

**Caution: Silicone based lubricants are not allowed in some facilities. Do not use with CPVC Products.**

©Teflon is a registered trademark of Dupont.

# Gruvlok® SPF/Anvil™ Lubricants

## Gruvlok® SPF/Anvil™ Quick Dry Lubricant

Gruvlok SPF/Anvil Quick Dry Lubricant is a fast drying lubricant that has been developed for applications where the piping system is exposed. The service temperature range for this lubricant is from 0° F to 150° F and may be used with all Gruvlok and SPF gasket material grades. The lubricant is made from a water emulsion that is non-toxic, it will not impart taste or odor, and does not support bacterial growth. Quick Dry Lubricant is non-corrosive, non-flammable, and is NSF approved for use with potable water.

This lubricant is easy to apply by brush or hand, and it quickly dries to a thin film when in contact with air. It is water-soluble. The quick drying quality of the lubricant eliminates lubricant drips caused by over lubrication. If necessary, reapply lubricant prior to assembly. Do not thin or mix with solvents.

## Gruvlok® SPF/Anvil™ Standard Lubricant

Gruvlok SPF/Anvil Standard Lubricant is the standard lubricant that has been provided for use with Gruvlok and SPF products for years. Gruvlok SPF/Anvil Lubricant is water soluble, non-toxic, non-corrosive, non-flammable, and will not impart taste or odor. It is NSF approved for use with potable water. This lubricant is acceptable for most applications, however, the Gruvlok SPF/Anvil Xtreme Lubricant and Gruvlok SPF/Anvil Quick Dry Lubricant are now available to improve the performance of the couplings and flanges in certain applications.

**Caution: HDPE pipe requires the use of Gruvlok SPF/Anvil Xtreme Lubricant and should not be used with Gruvlok SPF/Anvil Standard Lubricant.**



### Northern Region

Regional Distribution & Customer Service Center  
750 Central Avenue • University Park, IL 60484  
Tel: 708-885-3000 • Fax: 708-534-5441  
Toll Free: 1-800-301-2701

### Southern Region

Regional Distribution & Customer Service Center  
1401 Valley View Lane, Suite 150 • Irving, TX 75061  
Tel: 972-871-1206 • Fax: 972-641-8946  
Toll Free: 1-800-451-4414

[www.anvilintl.com](http://www.anvilintl.com)

#079 / Printed in USA / ©2011  
Revision Date: 6.17.11