

Part No.	Reference No.	Quantity	Description
4TXAUP2_4TXAUP2_153005~P	*		4TXAUP2 PARTS LIST
4TXA0002#4TXAUP2~S	*		COIL ACCESSORY
75008020#4TXAUP2~S	*		MODEL NUMBER DESCRIPTION

NO GRAPHIC AVAILABLE

75013702

REV
A

**NO
GRAPHIC
AVAILABLE**

Model Number Description		75008020	REV E
Heat Pump/Cooling Coil			
<p>Model No. 4TX C A O 36 A C 4 H C A A</p> <p>Digit No. 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15</p>			
<p>DIGIT 1 Refrigerant Type</p> <p>2 = R22</p> <p>4 = R410A</p>		<p>DIGIT 10 Efficiency</p> <p>C = Standard</p> <p>S = Hi Efficiency</p>	
<p>DIGIT 2 Product Family</p> <p>T = Premium (Heat Pump or Convertible Coil)</p> <p>C = Standard (Cooling only)</p>		<p>DIGIT 11 Flow Control</p> <p>2 = Capillary Tube</p> <p>3 = TXV - Non Bleed</p> <p>4 = Accutron Flow Control</p> <p>5 = TXV - Bleed</p> <p>6 = Fixed Orifice Accutron Flow Control</p>	
<p>DIGIT 3 Airflow</p> <p>X = Direct Expansion Evaporator Coil</p>		<p>DIGIT 12 Coil Circuitry</p> <p>H = Heat Pump</p> <p>C = Cooling Only</p> <p>D = Dual Circuit Cooling</p>	
<p>DIGIT 4 Product Family</p> <p>C = Cased Convertible A Coil</p> <p>A = Uncased A Coil</p> <p>F = Cased Horizontal Flat Coil</p>		<p>DIGITS 13 Airflow Application</p> <p>A = Upflow Only</p> <p>B = Upflow/Downflow</p> <p>H = Horizontal Only</p> <p>C = Convertible-Upflow, Downflow, Left Airflow</p> <p>M = Convertible-Upflow, Downflow, Left or Right Airflow</p>	
<p>DIGIT 5 Coil Width (Cased/Uncased)</p> <p>A = 14.5"/13.3"</p> <p>B = 17.5"/16.3"</p> <p>C = 21.0"/19.8"</p> <p>D = 24.5"/23.3"</p> <p>H = 10.5"</p>		<p>DIGIT 14 Minor Modification</p> <p>A = Minor Design Change</p>	
<p>DIGIT 6 Field Fitting</p> <p>O = Brazed</p>		<p>DIGIT 15 Service Digit</p> <p>A = Service Digit</p>	
<p>DIGITS 7 & 8 Capacity Nominal Capacity in 000's of BTUH's</p>			
<p>DIGIT 9 Major Modification</p> <p>A = Major Design Change</p>			

Part No.	Reference No.	Quantity	Description
75008020_4TXAUP2_153008~P	*		MODEL NUMBER DESCRIPTION PARTS LIST

Model Number Description		75008020	REV E
Heat Pump/Cooling Coil			
<p>Model No. 4TX C A O 36 A C 4 H C A A</p> <p>Digit No. 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15</p>			
<p>DIGIT 1 Refrigerant Type</p> <p>2 = R22</p> <p>4 = R410A</p>		<p>DIGIT 10 Efficiency</p> <p>C = Standard</p> <p>S = Hi Efficiency</p>	
<p>DIGIT 2 Product Family</p> <p>T = Premium (Heat Pump or Convertible Coil)</p> <p>C = Standard (Cooling only)</p>		<p>DIGIT 11 Flow Control</p> <p>2 = Capillary Tube</p> <p>3 = TXV - Non Bleed</p> <p>4 = Accutron Flow Control</p> <p>5 = TXV - Bleed</p> <p>6 = Fixed Orifice Accutron Flow Control</p>	
<p>DIGIT 3 Airflow</p> <p>X = Direct Expansion Evaporator Coil</p>		<p>DIGIT 12 Coil Circuitry</p> <p>H = Heat Pump</p> <p>C = Cooling Only</p> <p>D = Dual Circuit Cooling</p>	
<p>DIGIT 4 Product Family</p> <p>C = Cased Convertible A Coil</p> <p>A = Uncased A Coil</p> <p>F = Cased Horizontal Flat Coil</p>		<p>DIGITS 13 Airflow Application</p> <p>A = Upflow Only</p> <p>B = Upflow/Downflow</p> <p>H = Horizontal Only</p> <p>C = Convertible-Upflow, Downflow, Left Airflow</p> <p>M = Convertible-Upflow, Downflow, Left or Right Airflow</p>	
<p>DIGIT 5 Coil Width (Cased/Uncased)</p> <p>A = 14.5"/13.3"</p> <p>B = 17.5"/16.3"</p> <p>C = 21.0"/19.8"</p> <p>D = 24.5"/23.3"</p> <p>H = 10.5"</p>		<p>DIGIT 14 Minor Modification</p> <p>A = Minor Design Change</p>	
<p>DIGIT 6 Field Fitting</p> <p>O = Brazed</p>		<p>DIGIT 15 Service Digit</p> <p>A = Service Digit</p>	
<p>DIGITS 7 & 8 Capacity Nominal Capacity in 000's of BTUH's</p>			
<p>DIGIT 9 Major Modification</p> <p>A = Major Design Change</p>			

COIL ACCESSORY

Parts List Number :4TXAUP2#4TXAUP2

Model Number :4TXAD064BC3HUAA

Part No.	Reference No.	Quantity	Description
4TXA0002_4TXAUP2_407190~P	*		COIL ACCESSORY PARTS LIST

NO GRAPHIC AVAILABLE

75013702

REV
A

**NO
GRAPHIC
AVAILABLE**

Part No.	Reference No.	Quantity	Description
COL15145	1	1	COIL; UNCASSED ASSEMBLY, R410A REFRIGERANT (4TXAD064BC3HUAA)
VAL08634	2	1	VALVE; THERMOSTATIC EXPANSION W/MECHANICAL FITTINGS, R410 REFRIGERANT, 5 TON, NON-BLEED PORT, 90/86 PSIG SUPER HEAT, INTERNAL CHECK VALVE, .125 OD X 20.00 LONG EXTERNAL EQUALIZER
DST00875	3	1	DISTRIBUTOR; 5/8 - 20 THREADED .28 MFL INLET, 8 OUTLETS AT .19 ODF
PAN02734	4	1	PAN; DRAIN, PLASTIC, 23.28 X 21.04 X 2.03