

CONDUIT, FITTINGS, CABLE

Liquid Tite Flexible Conduit

Specifically for electrical applications. For outside, inside and industrial uses including transformer connections, air conditioning and heating. Joins with metallic or non-metallic connectors, easy to cut. Conduit is impact resistant, chemical resistant and will not kink. U.L. and C.U.L. Listed. For use as indicated in Article 351 of the 1987 NEC.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-12100	1/2" x 100' Liquid Tite Conduit – Non-Metallic	100' Roll
750-34100	3/4" x 100' Liquid Tite Conduit – Non-Metallic	100' Roll
750-10100	1" x 100' Liquid Tite Conduit – Non-Metallic	100' Roll
750-1550	1-1/2" x 50' Liquid Tite Conduit – Non-Metallic	50' Roll
750-2050	2" x 50' Liquid Tite Conduit – Non-Metallic	50' Roll
750-500	1/2" x 100' Liquid Tite Conduit – Metallic	100' Roll
750-600	3/4" x 100' Liquid Tite Conduit – Metallic	100' Roll

BX Set Screw Connectors

BX cable range = .445 to .630 diameter. U.L. Listed. CSA Approved.



CATALOG NO.	DESCRIPTION	STANDARD PACK
640-845	Trade Size – 3/8"	100

Aluminum Armored MC Cable

90°, C Rated aluminum metal clad cable system. THHN solid copper with specially compounded heat-resistant U.L. Listed insulation and jacket. Flexible interlocked aluminum armor. Extremely durable – withstands severe handling. U.L. Listed #4. Conforms to NEC article 333.



CATALOG NO.	DESCRIPTION	STANDARD PACK
640-122	12-2 Aluminum Armored MC Cable – 100' Roll	1
640-123	12-3 Aluminum Armored MC Cable – 100' Roll	1
640-142	14-2 Aluminum Armored MC Cable – 100' Roll	1
640-143	14-3 Aluminum Armored MC Cable – 100' Roll	1

EMT (Thinwall) Fittings



CATALOG NO.	DESCRIPTION	STANDARD PACK
625-800	Set Screw Connector – 1/2"	50
625-801	Set Screw Connector – 3/4"	25
625-304	Strap-One Hole – 1/2"	100
625-305	Strap-One Hole – 3/4"	100
625-810	Set Screw Coupling – 1/2"	50
625-811	Set Screw Coupling – 3/4"	25

Liquid Tite Connectors

For use with metallic and non-metallic liquid tite conduit, Type B. Provides smooth connection, no sharp edges to strip wire. Wiring easily pulled through. U. L. Listed. C.U.L. Listed.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-NMLT50	1/2" Non-Metallic Straight Connector	25
750-NMLT4550	1/2" Non-Metallic 45 Degree Elbow Connector	10
750-NMLT9050	1/2" Non-Metallic 90 Degree Elbow Connector	10
750-NMLT75	3/4" Non-Metallic Straight Connector	10
750-NMLT4575	3/4" Non-Metallic 45 Degree Elbow Connector	10
750-NMLT9075	3/4" Non-Metallic 90 Degree Elbow Connector	10
750-NMLT100	1" Non-Metallic Straight Connector	5
750-NMLT90100	1" Non-Metallic 90 Degree Elbow	5
750-NMLT150	1-1/2" Non-Metallic Straight Connector	5
750-NMLT90150	1-1/2" Non-Metallic 90 Degree Elbow	5
750-NMLT200	2" Non-Metallic Straight Connector	5
750-NMLT90200	2" Non-Metallic 90 Degree Elbow	5
750-MLT50	1/2" Metallic Straight Connector	25
750-MLT9050	1/2" Metallic 90 Degree Elbow	10
750-MLT75	3/4" Metallic Straight Connector	10
750-MLT9075	3/4" Metallic 90 Degree Elbow	10

Single Piece Liquid Tite Fittings

Conduit threads onto ferrule and up inside the outer body. An inside taper squeezes down on the outside of conduit for a superior liquid tight seal. The cut portion of the conduit does not show, giving a more finished appearance. Easy to use at a lower cost than regular liquid tite fittings.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-SLTC50	1/2" Straight Screw-On Fitting	25
750-SLTC9050	1/2" 90° Screw-On Fitting	25
750-SLTC75	3/4" Straight Screw-On Fitting	25
750-SLTC9075	3/4" 90° Screw-On Fitting	25

Romex Connectors – Metallic

Cable connectors for Romex Wire. Zinc die-cast.



CATALOG NO.	DESCRIPTION	STANDARD PACK
750-RC841	3/8" Romex Connector for 1/2" Knockouts	100
750-RC842	3/4" Romex Connector for 3/4" Knockouts	50

U.L. Listed and C.S.A. Approved.