

pullout disconnect w/GFCI receptacle

The MARS-2 Disconnect w/ GFCI Receptacle provides a convenient low cost means to satisfy NEC 2003 code changes requiring that a GFCI receptacle with a "while in use" cover be within a 25ft line of sight of the condenser unit. The pre-wired receptacle with stripped wire ends makes installation of Disconnect and Receptacle quick and easy. This unit provides a significantly lower "installed cost" to the contractor when compared to installing a standard disconnect and separate GFCI receptacle with "while in use" cover to comply with the new NEC code change.

Additional features and benefits include: Convenient electrical power cord channel w/retaining clip for easy and safe use of portable tools; Large wiring compartment for both disconnect switch and receptacle; Angled Receptacle mounting to eliminate the possibility of crushing portable electrical plugs when closing "while in use" cover; Attractive side opening cover design for ease of installation; Ultra UV powder coating.

specifications:

- 60 Amp, Non-Fused
- Pullout Type
- Pre-wired 15A, 125V GFCI Receptacle Included
- 240 Volt, Single Phase
- 10,000 Amp Rated
- NEMA 3R & UL Rainproof
- UL & CUL Approved
- Rated for 10HP @ 240 volts
- Meets NEC #210.63 & #406.8(B)(1)
- Multiple Patents Pending

Mars 2 No.	DESCRIPTION	STD. PACK	CASE QTY.
80308	Pullout Disconnect Receptacle	6	6

