


Switching Relays

MARS SERIES **902**




92340

2PDT HVAC Relays

MARS2 2PDT relays are primarily used for various applications in heating, air conditioning and refrigeration. They are also suitable for general purpose switching applications in appliances, vending machines, fan controls, and business machines provided the device being controlled is within the electrical limits of the relay.

Features:

- Replaces Honeywell, White-Rodgers/RBM
- 2.13 x 1.88 x 2.25 inches
- Quick-connect terminals
- Base designed for easy replacement of competitive relays
- Molded terminal numbers and circuit diagram on top of relay
- UL and CUR



COIL

Terminals 1 & 2, 4 & 5 are normally closed
Terminals 1 & 3, 4 & 6 are normally open

Contact Rating

	POWER 208/240V		PILOT 208/240V	
	120V	277V	120V	277V
Full load Amps	12	6	-	-
Resistive	15	15	3	3
Locked Rotor Amps	60	35	-	-
Horsepower	3/4	3/4	1/10	1/10

MARS2 NO.	COIL VOLTAGE	TERMINALS 1-2-3	TERMINALS 4-5-6	CROSS REFERENCE ESSEX / RBM	HONEYWELL
92340	24			90-340	R8222D1014
92341	110/120	Power	Power	90-341	R4222D1013
92342	208/240			90-342	R4222N1021