

ARM Control Expandable Zone Relays 2, 3, 4 and 6 Zone Controls



SWITCHING RELAYS & ACCESSORIES

ARM4P



MODEL	ZONES	TRANSFORMER VOLTAGE
ARM2P	2	120 VAC, 60 Hz, 20 VA
ARM3P	3	120 VAC, 60 Hz, 30 VA
ARM4P	4	120 VAC, 60 Hz, 30 VA
ARM6P	6	120 VAC, 60 Hz, 30 VA

Features:

- Priority Safety Timer - Ensures Other Zones Get Heat Every 30 Minutes & Prevents Freeze-ups
- 5-second Time Delay for Boiler Shut-off
- Premium plug-in replaceable relays
- Electronic Fuse - Auto Reset
- 30VA Transformer*† - Robust Enough to Handle up to 15 Zones
- 24 VAC Transformer Terminals
- Plug-in, Add-on Zone Modules (AD-1 or AD-4)
- Double-sided printed circuit board construction - 100% Factory Tested For Reliability
- Switchable Priority
- High relay load rating - 7.2 Amp / 1/3HP
- CSA listed
- Separate xx (isolated switch) & ZC/ZR Relays protect Boiler Aquastat.
- Relay Diagnostic Light - Easily Seen Through Window On Cover
- Clearly marked Terminals With Clamping Plates

* ARM-2P uses 20 VA Transformer. † Requires dry contact type thermostat or use of IR822 Isolation Relay

AD-4 Add-On Zoning Modules For ARM Relay Control



SPECIFICATIONS:

MODEL	ZONES	TRANSFORMER VOLTAGE	SWITCHING ACTION	THERMOSTAT CURRENT	SINGLE PHASE MOTOR RATING 120V AC
AD-1	1	N/A	0.085	SPST	1/3HP
AD-4	4	N/A	0.085	SPST	1/3HP

DPM2 Outdoor Reset Control

The DPM2 monitors outside temperature and adjusts boiler water temperature to match the outdoor demand – maximizing efficiency and reducing fuel usage.



- Can be used with any Argo Relay or Zone Value Control
- Or can work with most competitors' relays
- Reduces heating costs an average of 10% to 15% a year (depending on climate).

Standard Equipment:

