

Accessories

METER NUTS

Meter Nuts are used to connect straight and/or offset swivel gas fittings to the gas meter. Manufactured per ANSI B109.1.



Black Part #	Galvanized Part #	Size	Threads Per Inch	I.D. DIM. In Inches	Carton PCS/WT
4815-671	4815-673	5LT	12	0.880"	100/13
4815-501	4815-517	10LT	11 1/2	1.16"	100/18
4815-507	4815-523	20LT	11 1/2	1.42"	100/22
4815-543	4815-557	30LT	11 1/2	1.69"	100/30
4815-513	4815-529	1A	12	1.34"	100/24
4815-564	4815-574	0 EMCO	11 1/2	1.34"	100/24

Black Part #	Galvanized Part #	Size	Threads Per Inch	I.D. DIM. In Inches	Carton PCS/WT
4815-566	4815-576	45LT	11 1/2	1.94	100/42
4815-624	4815-626	3A/4A	11 1/2	2.02	50/37
4815-830	4815-832	60LT	11 1/2	1.94	50/24
4815-806	NA	5A	8	2.97	20/36
4815-700	NA	100LT	11	2.438	20/26

METER PLUGS

Meter Plugs are used to prevent the unintentional flow of gas from meter sets without meters attached. They also prevent insects and other foreign material from entering the gas piping. They are available as shown, or can be supplied with 1/8" or 1/4" pipe taps in the center of the hex, with or without standard pipe plugs.



Not Tapped	1/8" Part #	1/4" Part #	Size	Threads Per Inch	Carton PCS/WT
4820-181	4820-000	4820-195	10LT	11 1/2	100/21
4820-180	4820-002		#1A	12	100/26
4820-182	4820-001	4820-196	20LT	11 1/2	100/30
4815-663	4815-750	4820-014	30LT	11 1/2	100/41
4815-665	4815-769		45LT	11 1/2	100/48

GASKETS FOR SWIVELS

Gaskets are used to seal malleable iron offset or straight fittings on the face of the gas meter when tightening the swivel nut on meter thread or meter nut plug. These rubber gaskets made of Buna-N or neoprene are resistant to the action of natural and manufactured gases. The inside diameter is intended to lightly grip the pilot O.D. of the fitting to minimize problems during assembly of the swivel nut to the meter.



Model	Size	I.D. DIM. In Inches	O.D. DIM. In Inches	Thickness	Carton PCS/WT
4820-197	5LT	.72	.94	.109	100/10
4820-184	10LT	.968	1.251	.109	100/30
4820-185	Sprague #1A and O Emco	.968	1.406	.109	100/40
4820-186	20LT	1.290	1.625	.109	100/40
4820-187	30LT	1.468	1.875	.109	50/25

Model	Size	I.D. DIM. In Inches	O.D. DIM. In Inches	Thickness	Carton PCS/WT
4820-188	45LT	1.672	2.094	.109	50/30
4820-193	2A	1.118	1.718	.109	50/40
4820-190	3A / 4A	1.47	2.13	.109	50/40
4820-191	5A	2.295	3.232	.109	50/40
4820-192	60LT	1.88	2.29	.109	50/30

METER ADAPTERS - ZINC

The McDonald Meter Adapters are used to efficiently convert from one meter size to another. Each adapter comes with a flat gasket seal on the female end. In addition, each fitting is zinc plated for corrosion protection. The zinc is applied after machining so the threads are also protected.



Model	Male Meter Thread (converting from)	Female Meter Thread (converting to)	Carton PCS/WT
4820-007	10LT	20LT	50/30
4820-008	1A	10LT	50/18
4820-013	10LT	1A	50/17

If you are converting meter sizes in your system, consider these fittings for a cost effective approach. Manufactured per ANSI B109.1.