



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



SPECIALTY DOORS

Airtight/Watertight

ADWT

Application

- This access door is ideal for use in laboratories, clean rooms, operating rooms, etc. where an airtight/watertight seal is required

Product Features

- ADWT is a flush access door that has been tested for air infiltration and water penetration
- Door and Frame fully welded
- Continuous Bulb Trim Gasket
- Continuous Stainless Steel Piano Hinge
- Air Infiltration : less than 0.01 cfm/sq foot – ASTM E 283
- Water Penetration : no leakage at 15.05 psf – ASTM E 331

ADWT Access Door Specifications:

- Door / Door Frame:** Flush to frame with reinforced edges
Stainless Steel or Steel: 16 gauge door; 16 gauge mounting frame
- Hinge:** Continuous exposed stainless steel piano hinge
- Gasket:** Continuous Bulb Trim Seal
- Standard Latch:** Stainless Steel phillips head screws standard
- Optional Latches/Locks:** stainless steel allen head screws, stainless steel spanner head screws
- Finish:** Stainless Steel ; #4 satin polish
Steel : 5 stage iron phosphate with prime coat of White alkyd baking enamel



AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR	
inches	mm	lbs.	kg.
12 x 12	305 x 305	8	3.6
14 x 14	356 x 356	11	5
18 x 18	457 x 457	15	6.8
24 x 24	610 x 610	22	10
24 x 36	610 x 914	29	13.1
30 x 30	762 x 762	32	14.5
30 x 48	762 x 1219	44	20

Wall or ceiling opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

