





100 CFM/1.5 Sones @ 0.10" SP., 30.5 Watts 87 CFM @ 0.25 SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 11" x 13 3/4".

Blower Wheel

Balanced polymeric dual inlet blower wheel $5\,^{13/32}$ " dia. x 4" depth, 30 paddles, secured in place using 8M hex nut.

Motor

Enclosed 4 pole electronically balanced permanently split capacitor motor (PSC); life time lubricated. Motor bearings - ball. Suitable for continuous operation. Rated 115/120 volts, 60 Hz.

Fan Housing

23 gauge galvanized steel housing, fully sealed. Overall dimensions $10^{7/8}$ " x $9^{3/8}$ " x $7^{7/8}$ ".

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area


For bathrooms up to 100 sq. ft. For other rooms up to 125 sq. ft.

Electrical Connections

1/2" electrical knockouts provided.

Single Pack Shipping Info

Box Dim: $14^{1/8}$ " x $11^{5/8}$ " x $9^{5/8}$ " UPC: 0-8316221012-8 Shipping Weight: 11.5 lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

The housing will mount in ceilings with at least 8" of clearance and through drywall thickness up to 3/4", with a rough-in opening of $11^{1/8}" \times 9^{5/8}"$. The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

EXPANDED PERFORMANCE												
								Sones	Sones	Fan Speed	Power	
	Static Pressure (inches of w.g.)							@ .1 SP	@ .25 SP	RPM	Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25					
Air Flow - CFM	104	102	100	99	98	95	90	1.5	1.5	1106	30.5	0.31

PROJECT	ст						ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY DATE				
FAN NUMBER N	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		







U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048 **Canada:** 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 Fax: (905) 456-1015

Specifications subject to change without notice.