





80 CFM/2.0 Sones @ 0.10" SP., 32.0 Watts 61 CFM @ 0.25 SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".

Blower Wheel

One piece polymeric wheel 51/8" diameter, 23/8" wide, with 48 fins.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

Fan Housing

PC/ABS polymeric, dimensions 81/2" x 91/8" x 43/4".

Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 65 sq. ft. For other rooms up to 85 sq. ft.

Single Pack Shipping Info

Box Dim: 11" x 12" x 6" UPC: 0-8316290302-0 Shipping Weight: 5¹/4 lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to $^{3}\!/_{4}$ ", with a rough-in opening of $8^{1}\!/_{2}$ " x $9^{1}\!/_{8}$ ".

EXPANDED PERFORMANCE													
1									Sones	Sones	Fan Speed	Power	
1	Static Pressure (inches of w.g.)							@ .1 SP	@ .25 SP	RPM	Watts	Amps	
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3					
Air Flow - CFM	87	84	80	78	75	69	61	52	2.0	2.0	1347	32.0	0.3

PROJECT							ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY DATE				
FAN NUMBER N	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY		EQUIPMENT Marks	





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048 **Canada:** 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767 Fax: (905) 456-1015

Updated 8-12

Specifications subject to change without notice.