


HVAC Piping Insulation Protector



SUBMITTAL SHEET



Project	_____
Contractor	_____
Date	_____
Specification Reference	_____
Comments	_____



E-FLEX GUARD MODEL NUMBERS

Airex Part Number	Recommended Sizing Chart	
72E-B (6 ft)	Fits: 1/2" wall thickness pipe insulation with 5/8", 3/4", 7/8" tube.	8" Width
72C-B (6 ft)	Fits: 3/4" wall thickness pipe insulation with 5/8", 3/4", 7/8" tube or 1/2" wall thickness pipe insulation with 1-1/8" tube.	9.5" Width
72X-B (6 ft)	Fits: 1" wall thickness pipe insulation with 3/4", 7/8, 1-1/8" tube or 3/4" wall thickness pipe insulation with 1-1/8" tube.	11.5" Width

E-FLEX GUARD™	Black - B	White - W
Color Options		

Substitute White (W) for Black (B)

Product Description and Specification

AIREX E-FLEX GUARD™ - An insulation protective cover by Airex Manufacturing Inc., shall be provided and installed to be flexible, U/V and weather resistant. The PVC plastic pipe insulation cover shall feature an integrated, outdoor-rated durability, industrial-grade, full-enclosure fastening system that is double secured by molecular bonding, allowing custom, cut-to-length installations. The cut-to-length installations shall comprise of a non-unraveling PVC cover material that does not compromise long-term-effectiveness or require specialized tools and cutting equipment. The engineered fastening system is to allow the cover to be removable and reusable for maintenance without the use of adhesives as an attachment in any way shape or form, including either in the protector's construction, installation, or attachment to pipe insulation, as this will negatively affect insulation permeance performance and promote insulation material degradation which causes added energy usage by equipment. WRAPPING TAPE OR ADHESIVE TAPE SHALL NOT BE PERMITTED AS PER ENERGY CODES. Insulation Protector shall be tested and meet the following testing: ASTM E 96 (Vapor Transmission of Materials), ASTM G 153 (Carbon Arc Light Exposure – Accelerated Weathering), ASTM D 412 (Tensile Strength after UV Exposure and Water Immersion) ASTM 570 (Water Absorption of Plastics), ASTM E 84/UL 723 (Surface Burning Characteristics of Building Materials), ASTM G 21 (Fungal Growth). UV/Protector Pipe Insulation Material shall Meet Class II vapor retarder per ASTM E 96 (vapor/moisture permeability test) "1 perm or less". THE USE OF U/V PAINT OR NON-PERMEABLE MATERIALS OR ADHESIVES ARE NOT PERMITTED FOR THIS APPLICATION. **AIREX E-FLEX GUARD™** combines U/V weather and physical protection with a Class II rated vapor retarder permeability performance material, as required per energy codes.


Approved PVC Material Performance Testing

Material Testing Standards
<ul style="list-style-type: none"> • ASTM G153 – Weatherization and UV Exposure • ASTM E96 – Water/Vapor Permeability • ASTM G21 – Anti-Fungal/Anti-Microbial • ASTM D412 - Tension Deformation Test (UV Exposure & Water Immersion) • ASTM D570 – Water Absorption • ASTM E84/UL 723 - Flame and Smoke Rating 25/450



Airex Part Number	Recommended Sizing Chart	
750E-B (75 ft)	Fits: 1/2" wall thickness pipe insulation with 5/8", 3/4", 7/8" tube.	8" Width
750C-B (75 ft)	Fits: 3/4" wall thickness pipe insulation with 5/8", 3/4", 7/8" tube or 1/2" wall thickness pipe insulation with 1-1/8" tube.	9.5" Width
750X-B (75 ft)	Fits: 1" wall thickness pipe insulation with 3/4", 7/8, 1-1/8" tube or 3/4" wall thickness pipe insulation with 1-1/8" tube.	11.5" Width
750V-B (75 ft)	<p><i>Single Pipe</i> Fits: 3/4", 1" wall thickness pipe insulation with up to 2-1/8" tube, 3/4", 1" wall thickness pipe insulation with 1-3/8" tube, 1" wall thickness pipe insulation with 1-1/8" tube.</p> <p><i>Double Pipe</i> Fits: 1" wall thickness pipe insulation with 7/8" tube or 1" wall thickness pipe insulation with 3/8" tube.</p>	14.0" Width

90 Series 90° PVC Insulation Protectors



Airex Part Number	Recommended Sizing Chart
90E-B	90° Angle fits E Series
90C-B	90° Angle fits C Series
90X-B	90° Angle fits X Series

E-FLEX GUARD™	Black - B	White - W
Color Options		

Substitute White (W) for Black (B)



www.airexmfg.com

72170 Dunham Way, Suite D, Thousand Palms, CA 92276 Phone: (760) 343-2277 Fax: (760) 501-7912

U.S. Patents #9,091,377 B2, #9,523,200 B2

