

WAGS Product Spec Sheet The WAGS®

WAGS Valve sits in a drip pan under the water heater and is activated when leaking water accumulates to a predetermined level in the pan. Once activated, the industrial-duty, spring loaded piston in the valve shuts off the water flow, and the gas supply - if so equipped.



Materials Included in Box

- WAGS7200-4W (Water-Only Shutoff Valve) [Weight = 3.0 lb.]
- Instruction sheet • Required product sticker for water heater tank
- Warranty card & return envelope
- Drip Pan self-adhesive foam drain dam
- Condensation Drain Tube
- WAGS7200-5WG (Water & Gas Shutoff Valve) [Weight = 3.2 lb.]
- Gas or oil water heater assembly
- Wire harness - GASKIT7200-5WG
- Self-adhering mounting pad
- Wire tie

Specifications

General Information

Product: **WAGS Valve**

Ratings

- Valve Rating: 200 F - 2000 F
- Wire Assembly Rating: 5 – 35 Milli OHMS
- Maximum Operating Pressure: 80 PSI
- System Rating: 400 F - 1800 F
- Maximum Body Design Pressure: 125 psi

Dimensions: **WAGS VALVE:** 9" L x 2 3/4" H x 2 11/16" D

Box: 11" L x 4 1/2" H x 6 1/2" D

CSA - Prior Listing with Taco Inc.

NSF - Prior Listing with Taco Inc.

ROHS - Compliant

Certifications (Testing & Certifications done when manufactured & sold by Taco Inc. AQUAGUARD to reduce product cost not maintained, product design & manufacturing same as Taco Inc.'s no changes WAGS Valve still Certification compliant)